





REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------



Male(Front view)



B-code



B-code

1	brown
2	white
3	blue
4	black
5	gray
NO.	Color

- 1.RoHS Compliance,
- 2.The Code direction is shown as diagram,
- 3.Housing material: PU,(Color: black),
- 4.Contact body material: PU(Color: black)
- 5.Contact material: Copper alloy,(plating: gold)
- 6.O Ring material: Silicone,(Color: black)
- 7.M12–Screw material: Zinc alloy (plating: Ni),

Technique	parameter
-----------	-----------


Rated voltage	60V
Rated current	4A
Insulation resistance	$\geq 100\text{M}\Omega$
Withstanding voltage	1000VAC
Operating temperature	$-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$
Levels of protection	IP68
Cable OD	/

PART NO.:
FTM12B05MM12B05FQ0200

APPD:

ED	CHKD:
----	-------

DRFT: WYM 2019/05/23



THIRD ANGLE PROJECTION



DEGSON®

宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME:	
-------	--

FT-M12B-05M-M12B-05F-Q-0200

TITLE:	ASSEMBLY DRAWING
--------	------------------

REV	T0-1
-----	------

DRAWING NO.:	20000528
--------------	----------

SHEET	1/1
-------	-----

DO NOT SCALE DRAWING	SCALE	1:1
----------------------	-------	-----