




REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------




SPSH-M8A-XXP-MM-SF7003-00A(H)

Pin number:03,04



NOTES:

- 1.Rated voltage/current : 3pin:60V / 3A
4pin:60V / 3A
- 2.Withstanding voltage : 3,4pin:AC850V/1Min
- 3.Levels of protection:IP67
- 4.Wire connection mode:soldering(PCB)
- 5.Operating temperature: -40°C~+105°C
- 6.For Panel Thickness Range: 2.0~3.0mm
- 7.For PCB Thickness Max: 1.6mm
- 8.RoHS Compliance
- 9.Tolerance :
.X ±0.25mm
.XX ±0.1mm
L ±1°


3pin A Coding

Pin Assignment
Front View


4pin A Coding

Pin Assignment
Front View

PCB layout



PCB layout



Panel cut

DETACHED LISTS	PART NO.: SPSHM8AXXPMMSF700300AH	NINGBO DEGSON ELECTRICAL CO., LTD		
	APPD:	NAME: SPSH-M8A-XXP-MM-SF7003-00A(H)		
	CHKD:	TITLE: CUSTOMER DRAWING		
	DRFT: SQ 2019.05.17	REV D0-1		
THIRD ANGLE PROJECTION		DRAWING NO.: XXXXXXXX-XX-CXX	SHEET 1/1	
		MM (INCH)	DO NOT SCALE DRAWING	SCALE 1:1