

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Str. 1

D-78112 St. Georgen

Phone +49 (0) 7724 81-0

Fax +49 (0) 7724 81-1309

info2@de.ebmpapst.com

www.ebmpapst.com

**Nominal data**

| Type                     | REF 100-11/18     |          |
|--------------------------|-------------------|----------|
| Nominal voltage          | VDC               | 48       |
| Nominal voltage range    | VDC               | 36 .. 60 |
| Speed (rpm)              | min <sup>-1</sup> | 5400     |
| Power consumption        | W                 | 8.2      |
| Min. ambient temperature | °C                | -20      |
| Max. ambient temperature | °C                | 75       |
| Air flow                 | m <sup>3</sup> /h | 86       |
| Sound power level        | B                 | 6.3      |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



# DC centrifugal compact fan


single-intake

## Technical description

|                                         |                                                        |
|-----------------------------------------|--------------------------------------------------------|
| General description                     | Backward-curved impeller                               |
| Weight                                  | 0.160 kg                                               |
| Dimensions                              | Ø 100 x 25 mm                                          |
| Impeller material                       | Glass-fiber reinforced plastic                         |
| Housing material                        | Scroll housing made of glass-fiber reinforced plastic. |
| Airflow direction                       | Axial intake, radial discharge from outlet.            |
| Direction of rotation                   | Clockwise, viewed toward rotor                         |
| Storage                                 | Ball bearing                                           |
| Service life L10 at 40 °C               | 80000 h                                                |
| Service life L10 at maximum temperature | 30000 h                                                |
| Cable                                   | With leads AWG 22, TR 64                               |
| Motor protection                        | Protection against reverse polarity and blocked rotor. |
| Locked-rotor protection                 | With electronic locked-rotor and overload protection.  |
| Approval                                | CE                                                     |
| Option                                  | Speed signal                                           |



## Product drawing



# DC centrifugal compact fan

single-intake

## Curves: Air performance

