

AV000113

Connection technology • Cables (by the meter)

Accessories, cable tail, 3x0.22mm², silicone, gray, -40-180°C, by the meter



This connection cable can be ordered by the meter for individual cable lengths.
The silicone sheathing of the AV000113 comprises 3 cores, each with a cross-section of 0.22 mm².

Electrical features

Operating voltage (AC 50Hz)	500V
-----------------------------	------

Mechanical features

Core insulation material	plastic
Core identification	Color
Number of cores	3
Conductor cross-section	0.22mm ²
Outer diameter	5mm
Bending radius (flexible)	30mm
Bending radius (fixed)	20mm
Cable sheath color	Gray
Conductor category	Class 5 = flexible
Material of cable sheath	Silicone
Perm. ambient temperature of cable, fixed cable	-40 - 180°C
Perm. ambient temperature of cable, flexible cable	-25 - 180°C

Other features

Flame retardant	Yes
-----------------	-----

Classification

ETIM 8	EC003248 Power cable < 1 kV, for fixed installation
--------	---

More

IPF Product Group	854 cable, by meter
packaging dimensions	1105 x 180 x 100 mm
gross weight	1460 g
Customs tariff number	85444991
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Installation


Mounting / installation may only be carried out by a qualified electrician!

Disposal

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.