

AV000120

Connection technology • Cables (by the meter)

Accessories, cable tail, 5x0.34mm², PUR (polyurethane), shield, suitable for trailing chain, oils and cooling lubricants, by the meter



This connection cable can be ordered by the meter for individual cable lengths.

The plastic (PUR) sheathing of the AV000120 drag chain-capable cable comprises 5 cores, each with a cross-section of 0.34 mm².

Electrical features

Shielded	Yes
----------	-----

Mechanical features

Core identification	Color
Number of cores	5
Conductor cross-section	0.34mm ²
Conductor category	Class 6 = very flexible
Material of cable sheath	Plastic (PUR)
Suitable for trailing chain	Yes
UV-resistant	Yes

Other features

Oil and cooling lubricants	Yes
----------------------------	-----

Classification

ETIM 8	EC003248 Power cable < 1 kV, for fixed installation
--------	---

More

IPF Product Group	854 cable, by meter
packaging dimensions	
gross weight	50 g
Customs tariff number	85444991
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Extract accessories program**AV000130**

Tool, Wire stripper,
28x166x102mm, Skinning range
diameter 4.4-7mm, Plastic

AV000132

Tool, Wire stripper,
28x166x102mm, Skinning range
diameter 3.2-4.4mm, Plastic

You can find further accessories on our [homepage](#)

Installation

Mounting / installation may only be carried out by a
qualified electrician!

Disposal

Safety warnings

/ Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

/ Never use these devices in applications where the safety of a person depends on their functionality.