

AV000122

Connection technology • Cables (by the meter)

Accessories, cable tail, 5x0.34mm², PUR (polyurethane), equipment grounding conductor, suitable for trailing chain, oils and cooling lubricants, sold by the meter



This connection cable can be ordered by the meter for individual cable lengths.

The plastic (PUR) sheathing of the AV000122 drag chain-capable cable comprises 5 cores, each with a cross-section of 0.34 mm².

Electrical features

Equipment grounding conductor	Yes
-------------------------------	-----

Mechanical features

Core insulation material	Plastic (PP)
Core identification	Color
Number of cores	5
Wire assembly	42 x 0.1mm
Conductor cross-section	0.34mm ²
Outer diameter	5.2mm
Bending radius (flexible)	52mm
Bending radius (fixed)	26mm
Cable sheath color	black
Conductor category	Class 6 = very flexible
bending cycles	3 million cycles
Torsion cycles	+/-180°/m, ≥ 1 million cycles
Material of cable sheath	Plastic (PUR)
Perm. ambient temperature of cable, fixed cable	-40 - 90°C
Perm. ambient temperature of cable, flexible cable	-30 - 90°C
Suitable for trailing chain	Yes
Seawater-resistant	Yes
UV-resistant	Yes

Other features

Flame retardant	Yes
Ozone-resistant	Yes
Halogen-free	Yes
Hydrolysis-proof	Yes
Free of LABS	Yes
Welding area	Yes
Silicone-free	Yes
Acid and alkali-resistant	Yes
Oil and cooling lubricants	Yes

Classification

ETIM 8	EC003248 Power cable < 1 kV, for fixed installation
--------	---

More

IPF Product Group	854 cable, by meter
packaging dimensions	
gross weight	40 g
Customs tariff number	85444991
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Extract accessories program**AV000130**

Tool, Wire stripper,
28x166x102mm, Skinning range
diameter 4.4-7mm, Plastic

AV000132

Tool, Wire stripper,
28x166x102mm, Skinning range
diameter 3.2-4.4mm, Plastic

You can find further accessories on our homepage

Installation

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

I Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

I Never use these devices in applications where the safety of a person depends on their functionality.