

## VK150F76

### Connection technology • Cable sockets / connectors pre-assembled on two sides

Connection cable, 1.5m, M8 socket 3-pin straight, M8 connector 3-pin straight, 3x0.25mm<sup>2</sup>, PUR (polyurethane), IP67, LED, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free



ipf cable boxes are mainly used to establish the electrical connection of sensors. Their characteristics are characterized by the robust version, in highest protection classes (IP67 | IP68 | IP69K) and on request with 360° shielding. With the features: bus-compatible, drag chain and robot-compatible, oil-, chemical-resistant, welding spark-resistant, their detergent-resistant or resistance to high-pressure and steam jet cleaning, the extended temperature range up to +230°C, the rapid interconnection (technology) or special data transmission properties, the cable boxes meet all requirements of automation technology.

#### Electrical features

Display	LED display
Type of plug-in contact, A connection	Female (socket)
Type of plug-in contact, B connection	Male (connector)
Type of A electrical connection	M8
Type of B electrical connection	M8
Flow resistance	5mOhm
Line diameter	4mm
Number of pins of A connection	3
Number of pins of B connection	3
Operating voltage (DC)	30V

**Mechanical features**

Number of cores	3
Wire assembly	32 x 0.1mm
Conductor cross-section	0.25mm <sup>2</sup>
Cable sheath color	black
Cable length	1.5m
Cable infeed of A connection	straight
Cable infeed of B connection	straight
Maximum tightening torque of connection A	0.6Nm
Maximum tightening torque of connection B	0.6Nm
bending cycles	5 million cycles
Degree of protection (IP)	IP67
Torsion cycles	+/-360°/m, ≥ 2 million cycles
Contact coating material	Gold
Housing material	TPU
Material of cable sheath	Plastic (PUR)
Contact body material	Brass
Perm. ambient temperature of cable, fixed cable	-40 - 90°C
Perm. ambient temperature of cable, flexible cable	-25 - 60°C
Suitable for trailing chain	Yes
Material of the screw fitting	Brass
Ambient temperature	-30 - 90°C

**Optical features**

Degree of soiling	3
-------------------	---

**Other features**

Flame retardant	in accordance with EN 60332-2-2
Halogen-free	Yes
Hydrolysis-proof	Yes
Free of LABS	Yes
Ozone and UV-resistant	Yes
Suitable for trailing chain and torsion resistant	Yes
Welding area	Yes
Silicone-free	Yes
Oil and cooling lubricants	Yes
Version	Connection cable


**Classification**

ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--

## More

IPF Product Group	851 cable sockets / connectors (both side ready made)
packaging dimensions	160 x 160 x 20 mm
gross weight	
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

## Connection



## Installation



Mounting / installation may only be carried out by a qualified electrician!

## Disposal



## Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website [www.ipf-electronic.com](http://www.ipf-electronic.com).

**Dimensional drawing**