

## VK15E187

### Connection technology • Cable sockets / connectors pre-assembled on two sides

Connection cable, 1.5m, M8 socket 3-pin angular, Binder 680 connector 7-pin straight, 3x0.34mm<sup>2</sup>, PUR (polyurethane) black, Ø4.3mm, 30V, -30-85°C, IP67, 3A, LED, oils and cooling lubricants, welding area, silicone-free



ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

#### Electrical features

Display	LED display
Type of plug-in contact, A connection	Female (socket)
Type of plug-in contact, B connection	Male (connector)
Type of A electrical connection	M8
Type of B electrical connection	Binder 680
Flow resistance	10mOhm
Line diameter	4.3mm
Number of pins of A connection	3
Number of pins of B connection	7
Ampacity	3A
Operating voltage (AC 50Hz)	30V
Operating voltage (DC)	30V

**Mechanical features**

Number of cores	3
Wire assembly	42 x 0.1mm
Conductor cross-section	0.34mm <sup>2</sup>
Cable sheath color	black
Cable length	1.5m
Cable infeed of A connection	angular
Cable infeed of B connection	straight
Maximum tightening torque of connection A	0.5Nm
Degree of protection (IP)	IP67
Contact coating material	Gold
Material of cable sheath	Plastic (PUR)
Perm. ambient temperature of cable, fixed cable	-40 - 85°C
Perm. ambient temperature of cable, flexible cable	-30 - 85°C
Suitable for trailing chain	Yes
Material of the screw fitting	Brass
Ambient temperature	-30 - 85°C

**Optical features**

Degree of soiling	2
-------------------	---

**Other features**

Flame retardant	No
Halogen-free	Yes
Welding area	Yes
Silicone-free	Yes
Oil and cooling lubricants	Yes
Version	Connection cable


**Classification**

ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--

**More**

IPF Product Group	851 cable sockets / connectors (both side ready made)
packaging dimensions	220 x 160 x 20 mm
gross weight	65 g
Customs tariff number	85444290
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

## Connection



## Installation



Mounting / installation may only be carried out by a qualified electrician!

## Disposal



## Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website [www.ipf-electronic.com](http://www.ipf-electronic.com).

## Dimensional drawing

