

VK500A75

Connection technology • Cable sockets / connectors pre-assembled on one side

Connection cable, 5m, M8 Male (connector) 8pin Straight, A-coding, Free conductor end, 8x0.14mm², PUR (Polyurethane), -25-85°C, Silicone-free



ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: busready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

Electrical features

Type of plug-in contact, A connection	Male (connector)
Type of A electrical connection	M8
Type of B electrical connection	Free conductor end
Line diameter	5.9mm
Number of pins of A connection	8
Operating voltage (AC 50Hz)	60V
Operating voltage (DC)	60V

Mechanical features

Number of cores	8
Conductor cross-section	0.14mm²
Cable length	5m
Cable infeed of A connection	straight
Coding of connection A	Α
Maximum tightening torque of connection A	0.6Nm
Material of cable sheath	Plastic (PUR)
Material of the screw fitting	Brass
Ambient temperature	-25 - 85°C

Other features

Flame retardant	in accordance with EN 60332-2-2
Free of LABS	Yes
Silicone-free	Yes
Ambient temperature	-25 - 85°C
Version	Connection cable



Classification


ETIM 8	EC001855 Assembled sensor-actuator cable

More

IPF Product Group	850 cable sockets / connectors (one side ready made)
packaging dimensions	
gross weight	
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection

connector



- 2 brown
- 3 orange
- 4 violet
- 5 black
- 6 blue
- 7 yellow
- 1 red
- 8 green

Installation





Mounting / installation may only be carried out by a qualified electrician!



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.