

VK50E054

Connection technology • Cable sockets / connectors pre-assembled on two sides

Connection cable, 5m, M8 socket 4-pin angular, M8 connector 3-pin straight, 3x0.34mm², PUR (polyurethane) black, 30V, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free



This connection cable has pre-wired connections on both sides. It can be used to cost-effectively integrate end devices with a plug connection via a distribution terminal or a logic module.

Electrical features

Type of plug-in contact, A connection	Female (socket)
Type of plug-in contact, B connection	Male (connector)
Type of A electrical connection	M8
Type of B electrical connection	M8
Number of pins of A connection	4
Number of pins of B connection	3
Ampacity	4A
Operating voltage (AC 50Hz)	30V
Operating voltage (DC)	30V

Mechanical features

Number of cores	3
Conductor cross-section	0.34mm ²
Cable sheath color	black
Cable length	5m
Cable infeed of A connection	angular
Cable infeed of B connection	straight
Maximum tightening torque of connection A	0.6Nm
Maximum tightening torque of connection B	0.6Nm
bending cycles	5 million cycles
Torsion cycles	+/-360°/m, ≥ 2 million cycles
Material of cable sheath	Plastic (PUR)
Material of the screw fitting	Brass
Ambient temperature	-25 - 80°C

Other features


Flame retardant	in accordance with EN 60332-2-2
Halogen-free	Yes
Hydrolysis-proof	Yes
Free of LABS	Yes
Ozone and UV-resistant	Yes
Suitable for trailing chain and torsion resistant	Yes
Welding area	Yes
Silicone-free	Yes
Oil and cooling lubricants	Yes
Version	Connection cable

Classification


ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--

More

IPF Product Group	851 cable sockets / connectors (both side ready made)
packaging dimensions	200 x 200 x 30 mm
gross weight	295 g
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes


Connection

- 1** brown
2 n.c.
3 blue
4 black



- 1** brown
3 blue
4 black

Dimensional drawing




Extract accessories program

AV98F001



AV98F002



AV000117



Labeling material, Label, 2,
1x30x4mm, Plastic PC, 34
identification labels

AY000141



Plastic sheath, Ø17mm, Inner
diameter 10mm, -40-250°C, Glass
fiber with silicone rubber, Short-
term resistance to weld spatter
1200°C, Tensile strength 400N,
Flexible, Flame retardant, yard
good

AV000140



You can find further accessories on our homepage

Installation



Mounting / installation may only be carried out by a
qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.