

VKA0L375

Connection technology • Cable sockets / connectors pre-assembled on one side

Connection cable, 10m, M8 Female (socket) 4pin Straight, Free conductor end, 4x0.34mm², Other Gray, Ø4.6mm, 30V, -40-105°C, IP67, 4A, Suitable for trailing chain and torsion resistant



ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

Electrical features

Type of plug-in contact, A connection	Female (socket)
Type of cable	Multi-core
Type of A electrical connection	M8
Type of B electrical connection	Free conductor end
Flow resistance	5mOhm
Line diameter	4.6mm
Number of pins of A connection	4
Ampacity	4A
Operating voltage (AC 50Hz)	30V
Operating voltage (DC)	30V

Mechanical features

Number of cores	4
Wire assembly	42 x 0.1mm
Conductor cross-section	0.34mm ²
Cable sheath color	Gray
Cable length	10m
Cable infeed of A connection	straight
Maximum tightening torque of connection A	0.6Nm
Degree of protection (IP)	IP67
Contact coating material	Gold
Material of cable sheath	other
Contact body material	Brass
Perm. ambient temperature of cable, fixed cable	-40 - 105°C
Perm. ambient temperature of cable, flexible cable	-25 - 105°C
Suitable for trailing chain	Yes
Seawater-resistant	Yes
Material of the screw fitting	Stainless steel (V4A)
Ambient temperature	-40 - 105°C

Optical features

Degree of soiling	3
-------------------	---

Other features


Flame retardant	in accordance with EN 60332-1-2
Halogen-free	Yes
Hydrolysis-proof	Yes
Free of LABS	Yes
Ozone and UV-resistant	Yes
Suitable for trailing chain and torsion resistant	Yes
Acid and alkali-resistant	Yes
Ambient temperature	-40 - 105°C
Version	Connection cable

Classification

ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--

More

IPF Product Group	856 cable socket / cable connector (diverse)
packaging dimensions	191 x 191 x 30 mm
gross weight	2000 g
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection

- 1** brown
- 2** white
- 3** blue
- 4** black

Installation

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.