

VKBEC626

Connection technology • Cable sockets / connectors pre-assembled on one side

Connection cable, 25m, M12 Female (socket) 4pin Angular, Free conductor end, 4x0.34mm², PUR (Polyurethane), IP69K, Suitable for trailing chain and torsion resistant, Oil and cooling lubricants, Welding area, Silicone-free



ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

Electrical features

Type of plug-in contact, A connection	Female (socket)
Type of A electrical connection	M12
Type of B electrical connection	Free conductor end
Line diameter	6mm
Number of pins of A connection	4
Operating voltage (AC 50Hz)	60V
Operating voltage (DC)	60V

Mechanical features

Number of cores	4
Wire cross section	0.34mm ²
Cable length	25m
Cable infeed of A connection	angular
Maximum tightening torque of connection A	1Nm
bending cycles	5 million cycles
Degree of protection (IP)	IP69K
Torsion cycles	+/-360°/m, ≥ 2 million cycles
Material of cable sheath	PUR (Polyurethane)
Material of the screw fitting	Brass

Other features


Flame retardant	in accordance with EN 60332-2-2
Version	Connection cable
Halogen-free	Yes
Hydrolysis-proof	Yes
Free of LABS	Yes
Ozone and UV-resistant	Yes
Suitable for trailing chain and torsion resistant	Yes
Welding area	Yes
Silicone-free	Yes
Oil and cooling lubricants	Yes

Classification

ETIM 8	EC001855 Assembled sensor-actuator cable
eClass 7.0	27279218
eClass 7.1	27279218
eClass 8.0	27279218
eClass 9.0	27060311
eClass 9.1	27060311

More

IPF Product Group	850 cable sockets / connectors (one side ready made)
packaging dimensions	200 x 200 x 50 mm
gross weight	770 g
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection**Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.