

IB1201K2**Inductive sensors • atmospheric-change resistant**

sensor inductive, M12x1 63long, Flush, Sn: 2, 10-30V DC, -25-120°C, PNP NO, Cable 10m FEP, IP69K, V4A

including 2x Nut



Inductive proximity switches are contact-free sensors. They detect all conductive metals, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material and its dimensions. The vibration-resistant sensors can be approached laterally or frontally. Inductive proximity switches are used for presence detection (e.g. goods carriers), positioning (e.g. dampers), counting (e.g. nuts /bolts), speed detection (e.g. for cog wheels), on conveyor systems (e.g. hose feedings) or distance measurements (e.g. press-in checking) of metallic objects.

Electrical features

Type of switching function	Normally open contact (NO)
Type of electrical connection	Cable
Type of switching output	PNP
Rated switching current	200mA
Relative hysteresis	10%
Short-circuit protection	Yes
No-load current	4mA
Line diameter	4.6mm
Relative repeat accuracy	3%
Residual ripple	10%
Switching distance	2mm
Switching frequency	1000Hz
Voltage drop	2V
Reverse polarity protection	Yes
Operating voltage (DC)	10 - 30V

Mechanical features

Number of cores	3
Conductor cross-section	0.34mm ²
Alignment of cable entry	axial
Design	Cylinder, screw-thread
Pressure resistance	10bar
Thread length	35mm
Thread pitch	1mm
Cable length	10m
Cable infeed	axial
Length	63mm
Mechanical mounting condition for sensor	flush
Degree of protection (IP)	IP69K
Active area material of sensor	Plastic (PTFE)
Housing material	Stainless steel 1.4571
Material of cable sheath	Plastic (FEP)
Atmospheric-change resistant (temperature cycle)	Yes
Thread dimension	M12
Ambient temperature	-25 - 120°C

Other features


Oil and cooling lubricants	Yes
Reference medium / object	Standard measuring plate FE360 12x12x1mm
Ambient temperature	-25 - 120°C

Classification

ETIM 8	EC002714 Inductive proximity switch
--------	-------------------------------------

More

IPF Product Group	212 inductive sensors (unaffected by atmospheric changes)
packaging dimensions	210 x 138 x 95 mm
gross weight	378 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection

Installation

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.

Dimensional drawing