AbN automation

# KN126050

## **Capacitive sensors** • Increased ambient temperature

sensor capacitive, M12x1 25long, Non-flush, Sn: 1-25, 250°C, Amplifier Amplifier, Cable 2m FEP, IP67, Stainless steel 1.4305

including 2x Nut



Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.

### **Electrical features**

| Type of switching function    | Amplifier |
|-------------------------------|-----------|
| Type of electrical connection | Cable     |
| Type of switching output      | Amplifier |
| Short-circuit protection      | Yes       |
| Switching distance            | 1 - 25mm  |
| Reverse polarity protection   | Yes       |

#### **Mechanical features**

| Design                                   | Cylinder, screw-thread |
|--|------------------------|
| Thread pitch                             | 1mm                    |
| Cable length                             | 2m                     |
| Length                                   | 25mm                   |
| Mechanical mounting condition for sensor | non-flush              |
| Degree of protection (IP)                | IP67                   |
| Housing material                         | Stainless steel 1.4305 |
| Material of cable sheath                 | Plastic (FEP)          |
| Thread dimension                         | M12                    |
| Ambient temperature                      | 250°C                  |

#### Other features

| Level detection           | Yes                              |
|---------------------------|----------------------------------|
| Reference medium / object | Material with permittivity Er=81 |
| Ambient temperature       | 250°C                            |




#### Classification

| ETIM 8 | EC002715 Capacitive proximity switch |
|--------|--------------------------------------|
|        |                                      |

#### More

| IPF Product Group     | 242 capacitive sensors (high temperature) |
|-----------------------|---|
| packaging dimensions  | 123 x 77 x 25 mm                          |
| gross weight          | 80 g                                      |
| Customs tariff number | 85365019                                  |
| WEEE number           | 40951076                                  |
| Reach-compliant       | Yes                                       |
| RoHS-compliant        | Yes                                       |

## Connection



Installation Disposal



Mounting / installation may only be carried out by a qualified electrician!



## **Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.

### **Dimensional drawing**

