

OR255800

Optical sensors • Retro-reflective sensors

sensor optical, reflective, 88x63x24mm, Infrared light, Point, Manual adjustment, Sn: 8000, 12-265V AC/DC, Relay contact Change-over contact (NO/NC), Clamp 5pin, IP65, PA 6 (synthetic)+Plastic



Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

Electrical features

Display	LED display
Type of switching function	Change-over contact (NO/NC)
Type of electrical connection	Clamped terminal connection
Type of switching output	Relay contact
Turn-off delay	0 - 8ms
Rated switching current	3000mA
Readiness delay	60ms
Turn-on delay	0 - 10s
Setting procedure	Potentiometer
Short-circuit protection	No
No-load current	35mA
Number of pins	5
Switching distance	0 - 8000mm
Switching frequency	50Hz
Scanning function	Light-/dark-on mode
Reverse polarity protection	Yes
Absolute repeat accuracy	80mm
Operating voltage (AC 50Hz)	12 - 265V
Operating voltage (DC)	12 - 265V
Time function	Yes
Output functions	Switching point

Mechanical features

Design	Cuboid
Width	24mm
Height	88mm
Length	63mm
Degree of protection (IP)	IP65
Volume	Large
Active area material of sensor	Plastic
Housing material	PA 6 (synthetic)
Ambient temperature	-20 - 70°C

Optical features

Light source	Infrared light
Light beam form	Point
Wavelength of the sensor	880nm

Other features


Reference medium / object	AO000007
Ambient temperature	-20 - 70°C

Classification

ETIM 8	EC002717 Retro-reflective sensor
--------	----------------------------------

More

IPF Product Group	100 optical sensors
packaging dimensions	123 x 77 x 25 mm
gross weight	130 g
Customs tariff number	85365080
WEEE number	40951076
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection

Installation

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.

Dimensional drawing