

OS130074

Optical sensors • Through-beam sensors transmitters

Sensor Optical, through-beam sensor Transmitter, 89x12x12mm, Sn: 5m, 12-30V
diagnostic coverage, M8 connector 3-pin, IP67, aluminum anodized+plastic, infrared
light



Optical sensors work contactless. They detect objects, regardless of their properties (e.g. shape, color, surface structure, material). The basic mode of operation is based on the transmitter and receiver of light. There are three different versions: 1. the through-beam sensor consists of two separate devices, a transmitter and a receiver, which are aligned with each other. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. in the reflex light barrier, the transmitter and receiver are located in one device. The transmitted light beam is reflected onto the receiver by a reflector to be mounted opposite. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. the diffuse reflection sensor has a transmitter and receiver in one device. The transmitted light beam is reflected by the object to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

Electrical features

Display	LED display
Type of electrical connection	Connector M8
No-load current	30mA
Number of pins	3
Switching distance	0 - 5000mm
Reverse polarity protection	Yes
Operating voltage (DC)	12 - 30V

Mechanical features

Design	Cuboid
Width	12mm
Height	88.8mm
Storage temperature	-40 - 80°C
Length	12mm
Surface	Anodized
Degree of protection (IP)	IP67
Active area material of sensor	Plastic
Housing material	Aluminum
Ambient temperature	-20 - 60°C

Optical features

Light source	Infrared light
Light beam form	Point
Wavelength of the sensor	880nm
Angle of beam spread	6°

Other features


Features	with test input
Scope of delivery	Transmitter
Version	Through-beam sensor transmitter

Classification

ETIM 8

More

IPF Product Group	100 optical sensors
packaging dimensions	123 x 77 x 25 mm
gross weight	46 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection**Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.

Dimensional drawing

