

PR430270

Laser sensors • Retro-reflective sensors

sensor laser, reflective, 15x32x43mm, Laser diode, red light, Point, Teach-In, Sn: 5000, 10-30V DC, PNP NC (NC), Connector M8 4pin, IP67, Plastic+Glass, With polarizing filter



Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

Electrical features

Response/decay time	0.25ms
Type of switching function	Normally closed contact (NC)
Type of electrical connection	Connector M8
Type of switching output	PNP
Rated switching current	100mA
Setting procedure	Teach-In
Short-circuit protection	Yes
Laser power	1mW
No-load current	50mA
Number of pins	4
Switching distance	0 - 5000mm
Switching frequency	2000Hz
Voltage drop	2.2V
Scanning function	Light switching
Reverse polarity protection	Yes
Decay time	0.25ms
Absolute repeat accuracy	0.1mm
Operating voltage (DC)	10 - 30V
With polarizing filter	Yes

Mechanical features

Design	Cuboid
Width	43mm
Height	14.8mm
Length	32.5mm
Maximum tightening torque	0.8Nm
Degree of protection (IP)	IP67
Volume	Small
Active area material of sensor	glass
Housing material	Plastic
Ambient temperature	-10 - 50°C

Optical features

Laser class	Class 1
Light source	Laser diode, red light
Light beam form	Point
Min. object size	0.1mm
Wavelength of the sensor	650nm
focus	400mm
Light spot diameter at focal point	0.5mm

Other features


Ambient temperature	-10 - 50°C
---------------------	------------

Classification

ETIM 8	EC002717 Retro-reflective sensor
--------	----------------------------------

More

IPF Product Group	160 laser sensor
packaging dimensions	123 x 77 x 25 mm
gross weight	35 g
Customs tariff number	85365019
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection**Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.