

PT430470

Laser sensors • Diffuse reflection sensors with background suppression

sensor laser, diffuse-reflection sensor, 43x32x15mm, Sn: 20-350, 10-30V DC, 2x PNP NC/NO, Connector M8 4pin, IP67, Plastic+Plastic, 1kHz, Laser diode, red light, Point, Manual adjustment



Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

Electrical features

Response/decay time	0.5ms
Number of switching outputs	2
Display	LED display
Type of switching function	Normally closed contact/normally open contact
Type of electrical connection	Connector M8
Type of switching output	PNP
Rated switching current	100mA
Setting procedure	Manual adjustment
Short-circuit protection	Yes
Laser power	1mW
No-load current	35mA
Number of pins	4
Switching distance	20 - 350mm
Switching frequency	1000Hz
Voltage drop	2.2V
Scanning function	Light-/dark-on mode
Reverse polarity protection	Yes
Decay time	0.5ms
Absolute repeat accuracy	0.2mm
Operating voltage (DC)	10 - 30V

Mechanical features

Tightening torque	1Nm
Design	Cuboid
Width	14.8mm
Height	43mm
Length	32.5mm
Maximum tightening torque	0.8Nm
Degree of protection (IP)	IP67
Volume	Small
Active area material of sensor	Plastic
Housing material	Plastic
Ambient temperature	-10 - 50°C

Optical features

Laser class	Class 2
Light source	Laser diode, red light
Light beam form	Point
Wavelength of the sensor	650nm
focus	115mm
Light spot diameter at focal point	0.1mm

Other features


Operational mode	Background suppression
Reference medium / object	Material with 90% reflectivity
Ambient temperature	-10 - 50°C

Classification

ETIM 8	EC002719 Photoelectric proximity switch with background suppression
--------	---

More

IPF Product Group	160 laser sensor
packaging dimensions	123 x 77 x 25 mm
gross weight	33 g
Customs tariff number	85365019
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes
MTTFd	56 year(s)

Connection**Beam path****Installation**

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.

Dimensional drawing

