

UT089570**Ultrasonic sensors • Pushbuttons**

sensor ultrasonic, diffuse-reflection sensor, M8x1 70long, Sn: 20-100, 18-30V DC, 1x PNP/NPN Programmable/configurable, IO-Link, Connector M8 4pin, IP67, Brass Nickel-plated, Teach-In, With LED display, ultrasonic cone Axial

including 2x Nut



Ultrasonic sensors are non-contact and wear-free position switches which can also be used under rough environmental conditions. A key advantage of these devices lies in the fact that the material and the surface characteristics of the objects to be detected can be almost anything. Solids, liquids, grainy materials and powdery materials can be identified without the shape or the color of the object having any influence to the measured result. In addition, the ability to detect transparent materials such as films and fluids is of particular importance. The shape and color of the objects do not influence the result of the detection. The capability to detect transparent films or liquids is also of special importance. Ultrasonic sensors are used for distance measurement (e.g. detection of diameters, loop control), for fill level detection (e.g. silo detection), for positioning and presence detection (e.g. glass pane positioning, film tear check, glass bottle detection)

Electrical features

Response/decay time	10ms
Number of switching outputs	1
Display	LED display
Resolution	0.1mm
Type of switching function	Programmable/configurable
Type of electrical connection	Connector M8
Type of switching output	PNP/NPN
Rated switching current	150mA
Readiness delay	300ms
Setting procedure	Teach-In
Short-circuit protection	Yes
No-load current	30mA
Number of pins	4
Sound outlet	axial
Switching distance	20 - 100mm
Switching frequency	20Hz
Protection class	III
Voltage drop	2V
Temperature drift over entire measuring range	0.2%
Carrier frequency	484kHz
Reverse polarity protection	Yes
Absolute repeat accuracy	0.3mm
Operating voltage (DC)	18 - 30V

Mechanical features

Design	Cylinder, screw-thread
Thread length	47mm
Thread pitch	1mm
Length	70mm
Mounting distance	60mm
Surface	nickel-plated
Degree of protection (IP)	IP67
Housing material	Brass
Diameter detection	Yes
Thread dimension	M8
Ambient temperature	0 - 50°C

Other features


Operating frequency	484kHz
Level detection	Yes
Object detection on conveyor systems	Yes
Reference medium / object	Measuring plate 20x20mm
Ambient temperature	0 - 50°C

Classification

ETIM 8	EC001849 Ultrasonic probe
--------	---------------------------

More

IPF Product Group	250 ultrasonic sensors
packaging dimensions	155 x 175 x 8.5 mm
gross weight	29 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection

Installation

Mounting / installation may only be carried out by a qualified electrician!

Disposal**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website www.ipf-electronic.com.

Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com

Dimensional drawing