

MZ15C492

Magnetic field sensors • Sensors for trapezoidal groove

sensor magnetic, cylinder, Trapezoidal groove, 14x20x20mm, 10-30V DC, 1x PNP NO, Connector M8 3pin, IP67, Zinc die-cast, LED, 2.8mT, mounting From the top, Sensor surface position Center of the device



For many tasks in the field of automation technology, it is necessary to recognize the motional processes in pneumatic and hydraulic cylinders and to detect the position of the piston with precision. For this, magnetic cylinder sensors are used.

Electrical features

Number of switching outputs	1
Display	LED display
Type of switching function	Normally open contact (NO)
Type of electrical connection	Connector M8
Type of switching output	PNP
Rated switching current	150 mA
Absolute hysteresis	1 mm
Short-circuit protection	Yes
No-load current	15 mA
Magnetic sensitivity	2.8 mT
Number of pins	3
Switching frequency	1000 Hz
Sensor surface (active)	Middle area
Voltage drop	2 V
Reverse polarity protection	Yes
Absolute repeat accuracy	0.1 mm
Operating voltage (DC)	10 - 30 V
ardSOCA_ElektrischerAnschluss	M8 3-pin plug connector

Mechanical features

Design	Cuboid
Width	20 mm
Height	13.5 mm
Sensor surface position	Center of the device
Length	20 mm
Mounting access, cylinder groove	From the top
Degree of protection (IP)	IP67
Housing material	Zinc die-cast
Strong vibration / motion	Yes
Ambient temperature	-25 - 75 °C
ardSOCA_Abmessungen	20x20x13.5mm

Other features


Harsh environmental conditions	Yes
Oil and cooling lubricants	Yes




Classification

ETIM 8	EC002544 Magnetic proximity switch
--------	------------------------------------

More

IPF Product Group	223 pneumatic cylinder sensors (diverse)
packaging dimensions	120 x 100 x 30 mm
gross weight	14 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection

Dimensional drawing

Extract accessories program

VK030F82



Connection cable, 0.3m, M8
socket 3-pin angular, M12
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), IP67,
LED, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK060F82



Connection cable, 0.6m, M8
socket 3-pin angular, M12
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), IP67,
LED, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK200071



Connection cable, 2m, M8 Female
(socket) 3pin Angular, Free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, 60V, -
40-90°C, IP67, TPU, Suitable for
trailing chain and torsion resistant,
Oil and cooling lubricants, Welding
area, Silicone-free

VK200075



Connection cable, 2m, M8 female
(socket) 3pin Straight, free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, 60V, -
30-90°C, IP67, suitable for trailing
chain and torsion resistant, oil and
cooling lubricants, welding area,
Silicone-free

NG530002



DC power supply, single-phase,
99x114x22mm, 24V, 0.1A,
Number of relay outputs 2, 100-
264V AC 50Hz, 100-264V AC 60Hz,
Screw connection, IP20, Plastic,
Stabilized, Output voltage, pulsed

VK200271



Connection cable, 2m, M8 Female
(socket) 3pin Angular, Free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, -30-
90°C, IP67, With LED display,
Suitable for trailing chain and
torsion resistant, Oil and cooling
lubricants, Welding area, Silico...

VK500271



Connection cable, 5m, M8 Female
(socket) 3pin Angular, Free
conductor end 3pin, 3x0.34mm²,
PUR (Polyurethane), Ø4.3mm, -30-
90°C, IP67, With LED display,
Suitable for trailing chain and
torsion resistant, Oil and cooling
lubricants, Welding area, S...

VK30F70



Connection cable, 0.3m, M8
socket 3-pin angular, M8
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), 60V,
IP67, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK30F74



Connection cable, 0.3m, M8
socket 3-pin straight, M8
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), 60V,
IP67, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

You can find further accessories on our homepage



Installation

Mounting / installation may only be carried out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

I Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

I Never use these devices in applications where the safety of a person depends on their functionality.