

## MZA72126

### Magnetic field sensors • Sensors for T-slot

sensor magnetic, cylinder, 6.2mm T-groove, 4,3x19x6,2mm, 10-30V DC, 1x PNP NO, Cable connector M12 3pin 0.3m PUR (Polyurethane), IP67, Zinc die-cast, LED, 2.8mT, mounting From the top, Sensor surface position Center of the device



For many tasks in the field of automation technology, it is necessary to recognize the motional processes in pneumatic and hydraulic cylinders and to detect the position of the piston with precision. For this, magnetic cylinder sensors are used.

#### Electrical features

Number of switching outputs	1
Display	LED display
Type of switching function	Normally open contact (NO)
Type of electrical connection	Cable connector M12
Type of switching output	PNP
Rated switching current	150 mA
Absolute hysteresis	1 mm
Short-circuit protection	No
No-load current	15 mA
Magnetic sensitivity	2.8 mT
Number of pins	3
Switching frequency	1000 Hz
Sensor surface (active)	Middle area
Voltage drop	2 V
Reverse polarity protection	Yes
Absolute repeat accuracy	0.1 mm
Operating voltage (DC)	10 - 30 V
ardSOCA_ElektrischerAnschluss	Cable connector M12 3-pin 0.3m

**Mechanical features**

Design	Cuboid
Width	6.15 mm
Height	4.3 mm
Cable length	0.3 m
Sensor surface position	Center of the device
Length	19 mm
Maximum tightening torque	0.1 Nm
Mounting access, cylinder groove	From the top
Degree of protection (IP)	IP67
Housing material	Zinc die-cast
Material of cable sheath	Plastic (PUR)
Strong vibration / motion	Yes
Ambient temperature	-25 - 70 °C
ardSOCA_Abmessungen	19x6.15x4.3mm

**Other features**


Suitable for	6.2mm T-slot
Cylinder version	With T-groove
Harsh environmental conditions	Yes
Oil and cooling lubricants	Yes

**Classification**


ETIM 8	EC002544 Magnetic proximity switch
--------	------------------------------------

**More**

IPF Product Group	221 pneumatic cylinder sensors (low cost / reed)
packaging dimensions	120 x 100 x 20 mm
gross weight	18 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

**Connection**

## Dimensional drawing



## Extract accessories program

AY98A607



accessories sensor, Teflon cap,  
Ø16mm 16long, inner thread 12,  
Polytetrafluoroethylene (PTFE)

VY200120



time stage, Turn-on/turn-off  
delayed, Ø20mm 60long, 65s, 10-  
30V DC, 1x NO, M12 4pin, IP67,  
Plastic, Teach-In

VY030125



time stage, Turn-on delay, 0-0.15s,  
10-35V DC, 1x NO, M12 3pin 0.3m,  
IP67, Plastic, Potentiometer

AV000141



accessories cable socket,  
Mounting clip, 13.5mm, PPO,  
Packaging unit 5, Accessories for  
Cable socket/connector M12

AM98E153



accessories magnetic, Installation  
tape, 259x9,5mm, Span 35-68mm,  
For sensor MZ07, Stainless steel

AM98A882



accessories magnetic, For sensor  
MZ07, for Cylinder, Bosch profiled  
barrel, Screw mounting

AM000087



accessories magnetic, Cable clip,  
Plastic

AM000076



accessories magnetic, clamp, 4x6,  
2x6,2mm, aluminum

VY030224



Signal inversion, 10-35V DC, 1x  
NC/NO, M12 3pin 0.3m, IP67,  
Plastic

You can find further accessories on our homepage



## Installation

Mounting / installation may only be carried  
out by a qualified electrician!



## Disposal

WEEE number according to § 6 para. 3  
ElektroG: 40951076

## Safety warnings

**I** Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

**I** Never use these devices in applications where the safety of a person depends on their functionality.