

SY87F003

Flow sensors • Consumption measurement for various gases

Sensor flow, natural gas, calorimetric, G 1/2", 18-36V DC, 4-20mA, M12 connector
5pin, plastic PC, With display, parameterization, Ethernet, 200mbar



The function of the flow sensor is based on the calorimetric principle. The sensor is heated by a few degrees Celsius from the inside in relation to the flow medium into which it projects. When the medium flows, the heat generated in the sensor is dissipated by the medium. The temperature setting in the sensor is measured and compared with the medium temperature, which is also measured. From the temperature difference obtained, the flow condition can be derived for each medium. Applications for these sensors include measuring compressed air consumption.

Electrical features

Display	LED display
Type of analog output	4 - 20mA
Type of electrical connection	Connector M12
Type of interface connection	Plug-in connection M12
Setting procedure	Parameterization
Coding of interface connection	X-coded
Short-circuit protection	Yes
No-load current	140 mA
Number of pins	5
Reverse polarity protection	Yes
Measurement principle	calorimetric
Number of pins of interface connection	8
Supported communication interface	Ethernet Modbus RTU
Operating voltage (DC)	18 - 36 V
Optional: PoE (Power over Ethernet)	No
Measuring accuracy	± 1.5 % of measuring range ± 0.3 % of measuring range end

Mechanical features

Type of process connection	G1/2 inch
Design	Cuboid
Pressure resistance	50 bar
Length	220 mm
Probe length	220 mm
Medium temperature	-30 - 110 °C
Degree of protection (IP)	IP65
Housing material	Plastic PC
Sensing element material	Stainless steel 1.4301
with flow straightener	No
Measuring range flow velocity	,18 - 50 m/s
Ambient temperature	-20 - 70 °C

Other features

Suitable for	Gases
Mains pressure	200 mbar
Reference medium / object	Natural gas
Version	Insertion sensor
ardTE00_Anwendungen	Pneumatik-Anwendungen

Classification



ETIM 8	EC002580 Flow monitoring device
--------	---------------------------------

More

IPF Product Group	725 compressed air and leakage measurement
packaging dimensions	475 x 165 x 85 mm
gross weight	1150 g
Customs tariff number	90268020
WEEE number	40951076
RoHS-compliant	Yes

Important notes

I For pressure > 10 bar - order high-pressure safety device additionally

Connection**Dimensional drawing**

Extract accessories program**VK205621**

Connection cable, 2m, M12
Female (socket) 5pin Angular, Free
conductor end, 5x0.34mm², PUR
(Polyurethane), Ø6mm, 60V, -25-
90°C, IP67, Shielded, Suitable for
trailing chain and torsion resistant,
Oil and cooling lubricants, Welding
area, Silicone-free

VK205625

Connection cable, 2m, M12
Female (socket) 5pin Straight, Free
conductor end, 5x0.34mm², PUR
(Polyurethane), Ø6mm, 60V, -25-
90°C, IP67, Shielded, Suitable for
trailing chain and torsion resistant,
Oil and cooling lubricants, Welding
area, Silicone-...

AS000018

Accessories, high pressure safety
device for insertion sensor, sensor
length 220mm, max. 50bar

VK108F28

Data cable, Connection cable, 1m,
M12 Male (connector) 8pin
Straight, X-coding, RJ45 Male
(connector) 8pin Straight, 8x0.
14mm², Category 5E, -40-75°C,
TPU, Shielded

VKB08F28

Data cable, Connection cable,
20m, M12 Male (connector) 8pin
Straight, X-coding, RJ45 Male
(connector) 8pin Straight, 8x0.
14mm², Category 5E, -40-75°C,
TPU, Shielded

You can find further accessories on our homepage

**Installation**

Mounting / installation may only be carried
out by a qualified electrician!

**Disposal**

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

- I** Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.
- I** Never use these devices in applications where the safety of a person depends on their functionality.