

Technical data sheet Interconnection cable

Part no.: 50120463

KB 301-3000-MA200

Contents

- Technical data
- Electrical connection
- Accessories



For illustration purposes only



Technical data

Basic data

Suitable for interface	RS 232
------------------------	--------

Connection

Connection 1

Type of connection	Socket connector
No. of pins	32 -pin
Connector, LED	No

Connection 2

Type of connection	JST ZHR connector
No. of pins	10 -pin
	6 -pin

Cable properties

Number of conductors	16 Piece(s)
Sheathing color	Black
Shielded	Yes
Cable design	Interconnection cable
Cable diameter (external)	8.1 mm
Cable length	3,000 mm
Sheathing material	PVC
Suitability for drag chains	No

Classification

Customs tariff number	85444290
ECLASS 5.1.4	27279201
ECLASS 8.0	27279218
ECLASS 9.0	27060311
ECLASS 10.0	27060311
ECLASS 11.0	27060311
ECLASS 12.0	27060311
ECLASS 13.0	27060311
ECLASS 14.0	27060311
ECLASS 15.0	27060311
ETIM 5.0	EC001855
ETIM 6.0	EC001855
ETIM 7.0	EC001855
ETIM 8.0	EC001855
ETIM 9.0	EC001855
ETIM 10.0	EC001855

Electrical connection

Connection 1

Type of connection	Socket connector
No. of pins	32 -pin
Connector, LED	No

Connection 2

Type of connection	JST ZHR connector
No. of pins	10 -pin
	6 -pin

Accessories

Connection technology - Interconnection cables

	Part no.	Designation	Article	Description
   	50117011	KB USB A - USB miniB	Service line	Suitable for interface: USB Connection 1: USB Connection 2: USB Shielded: Yes Cable length: 1,500 mm Sheathing material: PVC

Accessories

Note	
	A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.