


50 ... 8000mm

- Laser diffuse sensor with large detection range for universal application (visible red light)
- Light propagation time measurement makes use possible under extreme environmental conditions (brightness, light, interfering contours)
- Extremely simple operation, teachable switching points
- Minimum teach duration prevents unintentional changing of the switching points
- Preset hysteresis and reserve ensure reliable switching behavior
- Switching behavior independent of the entry direction
- Optimized for positioning applications and reliable object detection (e.g. compartment occupation check, shelf positioning)


### Dimensioned drawing




### Electrical connection

HT10L1.3/L69-M12

HT10L1.3/L69,200-M12




HT10L1.3/L69




HT10L1.3/L66-M12

HT10L1.3/L66,200-M12




HT10L1.3/L66




HT10L1.3/L6X-M12

HT10L1.3/L6X,200-M12



HT10L1.3/L6X



### Accessories:

(available separately)

- Mounting systems
- Cable with M12 connector (K-D ...)
- IO-Link master set  
SET MD12-US2-IL1.1 + accessories - diagnostics set (part no. 50121098)

## Technical data

### Optical data

Typ. maximum range (white 90%) <sup>1)</sup>	50 ... 8000mm
Operating range <sup>2)</sup>	50 ... 3500mm
Adjustment range (teach-in range)	50 ... 8000/3500mm (90%/6% diffuse reflection)
Light source	Laser
Laser class	1 (in acc. with IEC 60825-1:2014)
Wavelength	658nm (visible red light)
Impulse duration	6ns
Max. output power (peak)	391mW
Light spot	Approx. 7x7mm <sup>2</sup> at 7m

### Error limits

Accuracy <sup>3)</sup>	± 30mm
B/W detection thresh. (6 ... 90% rem.)	± 10mm
Temperature drift	± 2mm/K

### Time behavior

Switching frequency	40Hz
Response time	< 50ms
Readiness delay	≤ 300ms

### Electrical data

Operating voltage $U_B$ <sup>4)</sup>	18 ... 30VDC (incl. residual ripple)
Residual ripple	≤ 15% of $U_B$
Open-circuit current	≤ 150mA
Switching output	.../...6... Push-pull switching output <sup>5)</sup> , PNP light switching, NPN dark switching ≥ $(U_B - 2V)/2V$ COM2 (38.4kBaud), vers. 1.1, min. cycle time 2.3ms, SIO is supported
Signal voltage high/low	
IO-Link	

### Indicators

Green/red LED	Green continuous light	Ready
	Red	No signal
	Orange	Warning, weak signal
	Off	No voltage
Yellow LEDs Q1/Q2	On	Object detected
	Off	Object not detected

### Mechanical data

Housing	Plastic
Optics cover	Glass
Weight	70g (M 12 connector) 133g (2m cable)
	90g (cable with M 12 connector)
Connection type	Turning M12 connector, 90° 2m cable, wire cross section 5 x 0.14mm <sup>2</sup> (5 x 26 AWG) 0.2m cable with M12 connector

### Environmental data

Ambient temp. (operation/storage)	-40°C ... +50°C/-40°C ... +70°C
Protective circuit <sup>6)</sup>	1, 2, 3
VDE protection class	III
Degree of protection	IP 67
Standards applied	IEC 60947-5-2
Certifications	UL 508, CSA C22.2 No.14-13 <sup>4)</sup> <sup>7)</sup>

### Additional functions

Deactivation input	
Transmitter inactive/active	≥ 8V/≤ 2V <sup>8)</sup>
Activation/disable delay	≥ 20ms
Input resistance	Approx. 10kΩ

- 1) Typ. maximum range: guaranteed operating range against 90% at maximum setting
- 2) Operating range: recommended range with function reserve
- 3) for measurement range 50 ... 3500mm, diffuse reflection 6% ... 90%, "Speed" operating mode, at 20°C after 20min. warmup time, medium range of  $U_B$ , measurement object  $\geq 50 \times 50 \text{ mm}^2$
- 4) For UL applications: use is permitted exclusively in Class 2 circuits according to NEC
- 5) The push-pull switching outputs must not be connected in parallel
- 6) 1=transient protection, 2=polarity reversal protection, 3=short circuit protection for all outputs
- 7) These proximity switches shall be used with UL Listed Cable assemblies rated 30V, 0.5A min, in the field installation, or equivalent (categories: CYJV/CYJV7 or PVVA/PVVA7)
- 8) Upon deactivation of the laser, the outputs become inactive


## Tables

Switching points <sup>1)</sup>	No reflection	Object detected
Yellow LED Q 1	Off	On
Yellow LED Q 2	Off	On

1) Applies for object teach

## Diagrams

Black/white behavior



A 6 ... 90% diffuse reflection

## Notes

### Adjusting the switching points

- **Object teach:**  
Align sensor with object.  
Q1: Press teach button 1 for approx. 2s,  
Q2: Press teach button 2 for approx. 2s,  
Q3: Press teach buttons 1+2 for approx. 2s.  
Switching point is taught.  
Object is detected if the respective Q1/Q2 indicator illuminates. No LED present for Q3.

- **Teach against background:**  
Point sensor at background.  
Q1: Press teach button 1 for approx. 7s,  
Q2: Press teach button 2 for approx. 7s,  
Q3: Press teach buttons 1+2 for approx. 7s.  
Switching point is taught.  
Objects between sensor and background are detected.

- **Hysteresis:**  
three selectable hysteresis settings (switchable via IO-Link):  
Coarse: 50mm (default)  
Medium: 25mm  
Fine: 12mm

- **Factory setting:**  
hysteresis: approx. 50mm
- With the set detection range, a tolerance of the upper scanning range limit is possible depending on the reflection properties of the material surface.
- Range/reflectivity:

Object/diffuse reflection	
6%	0.05 ... 3.5m
90%	0.05 ... 8m

### Observe intended use!

- ↳ This product is not a safety sensor and is not intended as personnel protection.
- ↳ The product may only be put into operation by competent persons.
- ↳ Only use the product in accordance with its intended use.

## Notes

- You can download the IO Device Description (IODD file) and the *Sensor Studio* configuration software (requires IO-Link USB master) from the Internet at [www.leuze.com](http://www.leuze.com).

## Laser safety notices

### ⚠ ATTENTION, LASER RADIATION – CLASS 1 LASER PRODUCT



The device satisfies the requirements of IEC/EN 60825-1:2014 safety regulations for a product of **laser class 1** and complies with 21 CFR 1040.10 except for conformance with IEC 60825-1 Ed. 3., as described in Laser Notice No. 56, dated May 8, 2019.

- ↳ Observe the applicable statutory and local laser protection regulations.
- ↳ The device must not be tampered with and must not be changed in any way.

There are no user-serviceable parts inside the device.

Repairs must only be performed by Leuze electronic GmbH + Co. KG.

## IO-Link process data format

(IO-Link 1.1, M-sequence TYPE\_2\_1)

### Output data device (8 bit)


Data bit								Assignment	Meaning
7	6	5	4	3	2	1	0		
								Switching output Q1	0 = inactive, 1 = active
								Switching output Q2	0 = inactive, 1 = active
								Switching output Q3	0 = inactive, 1 = active (if Q3 not present = 0)
								Measurement	0 = initialization/teach/deactivation, 1 = running measurement
								Signal	0 = no signal or signal too weak, 1 = signal ok
								Warning	0 = no warning, 1 = warning, e.g., weak signal
								0	Not assigned (initial state = 0)
								0	Not assigned (initial state = 0)

### Device input data

None

## Part number code

HT10L1.3/L69,200-M12



### Operating principle

HT Laser diffuse sensors with background suppression

### Series

10 10 series

### Laser class

L1 Laser class 1 (in acc. with IEC 60825-1:2014)

### Equipment

3 Membrane keyboard for teach-in

### Assignment pin 4

L IO-Link (with dual channel, also push/pull switching output)

### Assignment pin 2

6 Push/pull switching output

### Assignment pin 5

9 Deactivation input (factory setting) or teach input  
(> 8VDC, configurable)

6 Push/pull switching output

X Do not connect

### Electrical connection

-M12 M12 connector, 5-pin

,YYYY Cable, length YYYY mm with wire-end sleeves, 5-wire  
(no information = standard length 2000 mm)

,200-M12 Cable, length 200mm with M12 connector, 5-pin

## Order guide

	Designation	Part no.
<b>Connection: M12 connector, 5-pin</b>		
IO-Link 1.1/switching output, 1 push/pull switching output, deactivation input	HT10L1.3/L69-M12	50129537
IO-Link 1.1/switching output, 2 push/pull switching outputs	HT10L1.3/L66-M12	50129540
IO-Link 1.1/switching output, 1 push/pull switching output	HT10L1.3/L6X-M12	50128388
<b>Connection: cable, length 2000mm with wire-end sleeves, 5-wire</b>		
IO-Link 1.1/switching output, 1 push/pull switching output, deactivation input	HT10L1.3/L69	50129542
IO-Link 1.1/switching output, 2 push/pull switching outputs	HT10L1.3/L66	50129546
IO-Link 1.1/switching output, 1 push/pull switching output	HT10L1.3/L6X	50129543
<b>Connection: cable, length 200mm with M12 connector, 5-pin</b>		
IO-Link 1.1/switching output, 1 push/pull switching output, deactivation input	HT10L1.3/L69,200-M12	50129549
IO-Link 1.1/switching output, 2 push/pull switching outputs	HT10L1.3/L66,200-M12	50129551
IO-Link 1.1/switching output, 1 push/pull switching output	HT10L1.3/L6X,200-M12	50129548
<b>Accessories</b>		
Mounting system for mounting on rods Ø 10mm	BTU 460M-D10	50128379
Mounting system for mounting on rods Ø 12mm	BTU 460M-D12	50128380
Connection cable with M12 connector, angled, 5-pin, length 2m, PVC sheathing (many other connection cables are available)	K-D M12W-5P-2m-PVC	50104556
IO-Link master set	SET MD12-US2-IL1.1 + accessories - diagnostics set	50121098

## The following teach options are available:

The Q1, Q2 (Q3) switching outputs can be individually set.

	Teach options	Part designations
	<b>Standard teach (object teach)</b>	.../L6X_6_T..
Press	2 to 7 sec	
<b>Teach against background</b>		.../L6X_6_T..
Press	7 to 12 sec	
<b>Light/dark switching</b>		.../L6X_6_T..
Press	12 to 17 sec	
<b>Window teach</b>		.../L6T.P1..
<b>Upper limit</b>		
Press	7 to 12 sec	
<b>Lower limit</b>		
Press	12 to 17 sec	
<b>Teach against object</b>		
Press	up to 2 sec	

## Teach process for light/dark switching

The following processes are identical for Q1, Q2, (Q3).

Q1, Q2 (Q3) can be individually set.



LED	Status LED	2 sec	7 sec	12 sec	Release	Status LED
<b>1</b> Object is detected (distance to object $\leq$ set operating range)						
<b>Light</b>					$\rightarrow$	<b>Dark</b>
Green LED	On		Flash simultaneously	Flash alternately	Flashing On	On
Yellow LED	On				$\rightarrow$	Off
<b>Dark</b>						
Green LED	On		Flash simultaneously	Flash alternately	Flashing On	On
Yellow LED	Off				$\rightarrow$	On
<b>2</b> Object is not detected (distance to object $>$ set operating range + reserve + hysteresis)						
<b>Light</b>					$\rightarrow$	<b>Dark</b>
Green LED	On		Flash simultaneously	Flash alternately	Flashing On	On
Yellow LED	Off				$\rightarrow$	On
<b>Dark</b>					$\rightarrow$	<b>Light</b>
Green LED	On		Flash simultaneously	Flash alternately	Flashing On	On
Yellow LED	On				$\rightarrow$	Off