



Product designation	Power contactor		
Product type designation	B145		
Contact characteristics			
Number of poles	Nr.	3	
Rated insulation voltage U_i IEC/EN	V	1000	
Rated impulse withstand voltage U_{imp}	kV	8	
Operational frequency	min	Hz	25
	max	Hz	400
IEC Conventional free air thermal current I_{th}		A	250
Operational current I_e			
	AC-1 ($\leq 40^\circ C$)	A	250
	AC-1 ($\leq 55^\circ C$)	A	235
	AC-1 ($\leq 70^\circ C$)	A	190
	AC-3 ($\leq 440V \leq 55^\circ C$)	A	150
	AC-4 (400V)	A	57
Rated operational power AC-3 ($T \leq 55^\circ C$)	400V	kW	80
Rated operational power AC-1 ($T \leq 40^\circ C$)	230V	kW	91
	400V	kW	150
	500V	kW	196
	690V	kW	270
IEC max current I_e in DC1 with $L/R \leq 1ms$ with 1 poles in series	75V	A	220
	110V	A	110
	220V	A	—
	330V	A	—
	460V	A	—
IEC max current I_e in DC1 with $L/R \leq 1ms$ with 2 poles in series	75V	A	220
	110V	A	150
	220V	A	130
	330V	A	—
	460V	A	—
IEC max current I_e in DC1 with $L/R \leq 1ms$ with 3 poles in series	75V	A	220
	110V	A	150
	220V	A	150
	330V	A	130
	460V	A	—
IEC max current I_e in DC1 with $L/R \leq 1ms$ with 4 poles in series	75V	A	220
	110V	A	150
	220V	A	150

	330V	A	150
	460V	A	130
IEC max current le in DC3-DC5 with L/R ≤ 15ms with 1 poles in series			
	75V	A	160
	110V	A	80
	220V	A	—
	330V	A	—
	460V	A	—
IEC max current le in DC3-DC5 with L/R ≤ 15ms with 2 poles in series			
	75V	A	160
	110V	A	120
	220V	A	90
	330V	A	—
	460V	A	—
IEC max current le in DC3-DC5 with L/R ≤ 15ms with 3 poles in series			
	75V	A	160
	110V	A	140
	220V	A	120
	330V	A	90
	460V	A	—
IEC max current le in DC3-DC5 with L/R ≤ 15ms with 4 poles in series			
	75V	A	160
	110V	A	140
	220V	A	140
	330V	A	140
	460V	A	90
Short-time allowable current for 10s (IEC/EN60947-1)			A 1300
Protection fuse			
	gG (IEC)	A	250
	aM (IEC)	A	160
Making capacity (RMS value)			A 1500
Breaking capacity at voltage			
	440V	A	1500
	500V	A	1400
	690V	A	1200
Resistance per pole (average value)			m? 0.3
Power dissipation per pole (average value)			
	I _{th}	W	14.5
	AC3	W	6.8
Tightening torque for terminals			
	min	Nm	18
	max	Nm	18
	min	lbin	13.3
	max	lbin	13.3
Tightening torque for coil terminal			
	min	Nm	1
	max	Nm	1
	min	lbin	0.74
	max	lbin	0.74
Max number of wires simultaneously connectable			Nr. 2
Conductor section			
	AWG/Kcmil		
		max	4/0

Power terminal protection according to IEC/EN 60529	IP00					
Mechanical features						
Operating position						
Fixing	normal allowable	Vertical plan ±30°				
Weight		Screw	g 6250			
Conductor section						
AWG/kcmil conductor section	max	4/0				
Operations						
Mechanical life	cycles	10000000				
Electrical life	cycles	1100000				
Safety related data						
Performance level B10d according to EN/ISO 13489-1	rated load mechanical load	cycles	1100000 10000000			
Mirror contacts according to IEC/EN 609474-4-1		yes				
EMC compatibility						
AC coil operating						
Rated AC voltage at 50/60Hz, 60Hz	min max	V V	380 415			
AC operating voltage						
of 50/60Hz coil powered at 50Hz						
pick-up	min max	%Us %Us	80 110			
drop-out	min max	%Us %Us	20 60			
of 50/60Hz coil powered at 60Hz						
pick-up	min max	%Us %Us	80 110			
drop-out	min max	%Us %Us	20 60			
of 60Hz coil powered at 60Hz						
pick-up	min max	%Us %Us	80 110			
drop-out	min max	%Us %Us	20 60			
AC average coil consumption at 20°C						
of 50/60Hz coil powered at 50Hz	in-rush holding	VA VA	300 10			
of 50/60Hz coil powered at 60Hz	in-rush holding	VA VA	300 10			
Dissipation at holding ≤20°C 50Hz		W	10			

DC coil operating

DC rated control voltage

min	V	380
max	V	415

DC operating voltage

pick-up

min	%Us	80
max	%Us	110

drop-out

min	%Us	20
max	%Us	60

Average coil consumption $\leq 20^{\circ}\text{C}$

in-rush	W	300
holding	W	10

Max cycles frequency

Mechanical operation

cycles/h 2400

Operating times

Average time for Us control

in AC

Closing NO

min	ms	60
max	ms	100

Opening NO

min	ms	25
max	ms	60

in DC

Closing NO

min	ms	60
max	ms	100

Opening NO

min	ms	25
max	ms	60

UL technical data

Full-load current (FLA) for three-phase AC motor

at 480V	A	124
at 600V	A	125

Yielded mechanical performance

for three-phase AC motor

200/208V	HP	50
220/230V	HP	50
460/480V	HP	100

General USE

Contactor

AC current	A	250
------------	---	-----

Short-circuit protection fuse, 600V

Standard fault

Short circuit current	kA	5
Fuse rating	A	500
Fuse class		RK5

Ambient conditions

Temperature

Operating temperature

min	°C	-50
max	°C	70

Storage temperature

min	°C	-60
max	°C	80

Max altitude


m 3000

Resistance & Protection


Pollution degree

3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

[CSA C22.2 n° 60947-1](#)

[CSA C22.2 n° 60947-4-1](#)

[IEC/EN 60947-1](#)

[IEC/EN 60947-4-1](#)

[UL 60947-1](#)

[UL 60947-4-1](#)

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000066 -
Power contactor,
AC switching