



Product designation

Power contactor

Product type designation

BF18

Contact characteristics

Number of poles	Nr.	4
Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	6
Operational frequency	min Hz	25
	max Hz	400
IEC Conventional free air thermal current I_{th}	A	32
Operational current I_e	AC-1 (=40°C)	A 32
	AC-1 (=55°C)	A 26
	AC-1 (=70°C)	A 23
	AC-3 (=440V =55°C)	A 18
	AC-4 (400V)	A 8.5
Rated operational power AC-1 (T=40°C)	230V kW	12
	400V kW	21
	500V kW	26
	690V kW	36
IEC max current I_e in DC1 with L/R = 1ms with 1 poles in series	=24V A	17
	48V A	15
	75V A	15
	110V A	6
	220V A	–
IEC max current I_e in DC1 with L/R = 1ms with 2 poles in series	=24V A	20
	48V A	20
	75V A	20
	110V A	13
	220V A	1
IEC max current I_e in DC1 with L/R = 1ms with 3 poles in series	=24V A	22
	48V A	22
	75V A	20
	110V A	16
	220V A	11
IEC max current I_e in DC1 with L/R = 1ms with 4 poles in series	=24V A	22
	48V A	22
	75V A	20
	110V A	18
	220V A	13

IEC max current Ie in DC3-DC5 with L/R = 15ms with 1 poles in series

=24V	A	12
48V	A	11
75V	A	11
110V	A	2
220V	A	–

IEC max current Ie in DC3-DC5 with L/R = 15ms with 2 poles in series

=24V	A	15
48V	A	13
75V	A	13
110V	A	8
220V	A	2

IEC max current Ie in DC3-DC5 with L/R = 15ms with 3 poles in series

=24V	A	18
48V	A	18
75V	A	16
110V	A	12
220V	A	6

IEC max current Ie in DC3-DC5 with L/R = 15ms with 4 poles in series

=24V	A	18
48V	A	18
75V	A	16
110V	A	13
220V	A	8

Short-time allowable current for 10s (IEC/EN60947-1)

A	200
---	-----

Protection fuse

gG (IEC)	A	32
aM (IEC)	A	20

Making capacity (RMS value)

A	180
---	-----

Breaking capacity at voltage

440V	A	144
500V	A	120
690V	A	94

Resistance per pole (average value)

m?	2.5
----	-----

Power dissipation per pole (average value)

Ith	W	2.6
AC3	W	0.8

Tightening torque for terminals

min	Nm	1.5
max	Nm	1.8
min	lbin	1.1
max	lbin	1.5

Tightening torque for coil terminal

min	Nm	0.8
max	Nm	1
min	lbin	0.8
max	lbin	0.74

Max number of wires simultaneously connectable

Nr.	2
-----	---

Conductor section

AWG/Kcmil


max	10
-----	----

Flexible w/o lug conductor section


min	mm ²	1
-----	-----------------	---

	max	mm ²	6
Flexible c/w lug conductor section	min	mm ²	1
	max	mm ²	4
Flexible with insulated spade lug conductor section	min	mm ²	1
	max	mm ²	4
Power terminal protection according to IEC/EN 60529	IP20 when wired		
Mechanical features			
Operating position	normal allowable	Vertical plan ±30°	
Fixing			Screw / DIN rail 35mm
Weight		g	360
Conductor section	AWG/kcmil conductor section		
	max	10	
Operations			
Mechanical life		cycles	20000000
Electrical life		cycles	1600000
Safety related data			
Performance level B10d according to EN/ISO 13489-1	rated load mechanical load	cycles	1600000
		cycles	20000000
Mirror contats according to IEC/EN 609474-4-1			yes
EMC compatibility			yes
AC coil operating			
Rated AC voltage at 50/60Hz		V	230
AC operating voltage	of 50/60Hz coil powered at 50Hz		
	pick-up		
	min	%Us	80
	max	%Us	110
	drop-out		
	min	%Us	20
	max	%Us	55
	of 50/60Hz coil powered at 60Hz		
	pick-up		
	min	%Us	85
	max	%Us	110
	drop-out		
	min	%Us	20
	max	%Us	55
AC average coil consumption at 20°C	of 50/60Hz coil powered at 50Hz		
	in-rush holding	VA	75
		VA	9
	of 50/60Hz coil powered at 60Hz		
	in-rush holding	VA	70
		VA	6.5
	of 60Hz coil powered at 60Hz		
	in-rush holding	VA	75
		VA	9

Dissipation at holding =20°C 50Hz		W	2.5
Max cycles frequency			
Mechanical operation		cycles/h	3600
Operating times			
Average time for Us control in AC			
	Closing NO	min	ms 8
		max	ms 24
	Opening NO	min	ms 10
		max	ms 20
	Closing NC	min	ms 14
		max	ms 28
	Opening NC	min	ms 7
		max	ms 18
UL technical data			
Full-load current (FLA) for three-phase AC motor			
	at 480V	A	14
	at 600V	A	17
Yielded mechanical performance			
for single-phase AC motor			
	110/120V	HP	1
	230V	HP	3
for three-phase AC motor			
	200/208V	HP	5
	220/230V	HP	5
	460/480V	HP	10
	575/600V	HP	15
General USE			
Contactor			
	AC current	A	32
Short-circuit protection fuse, 600V			
High fault			
	Short circuit current	kA	100
	Fuse rating	A	60
	Fuse class		J
Standard fault			
	Short circuit current	kA	5
	Fuse rating	A	80
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-50
	max	°C	70
Storage temperature			
	min	°C	-60
	max	°C	80
Max altitude		m	3000
Resistance & Protection			
Pollution degree			3
Dimensions			



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1
CSA C22.2 n° 60947-4-1
IEC/EN 60947-1
IEC/EN 60947-4-1
UL 60947-1
UL 60947-4-1

Certificates

CCC
cULus
EAC

ETIM classification

ETIM 8.0

EC000066 -
Power contactor,
AC switching