



Product designation

Power contactor

Product type designation

BF25

**Contact characteristics**

|                                                                    |                    |         |
|--------------------------------------------------------------------|--------------------|---------|
| Number of poles                                                    | Nr.                | 3       |
| Rated insulation voltage $U_i$ IEC/EN                              | V                  | 690     |
| Rated impulse withstand voltage $U_{imp}$                          | kV                 | 6       |
| Operational frequency                                              | min                | Hz 25   |
|                                                                    | max                | Hz 400  |
| IEC Conventional free air thermal current $I_{th}$                 | A                  | 32      |
| Operational current $I_e$                                          | AC-1 (=40°C)       | A 32    |
|                                                                    | AC-1 (=55°C)       | A 26    |
|                                                                    | AC-1 (=70°C)       | A 23    |
|                                                                    | AC-3 (=440V =55°C) | A 25    |
|                                                                    | AC-4 (400V)        | A 10    |
| Rated operational power AC-3 (T=55°C)                              | 230V               | kW 7    |
|                                                                    | 400V               | kW 12.5 |
|                                                                    | 415V               | kW 13.4 |
|                                                                    | 440V               | kW 13.4 |
|                                                                    | 500V               | kW 15   |
|                                                                    | 690V               | kW 11   |
| Rated operational power AC-1 (T=40°C)                              | 230V               | kW 12   |
|                                                                    | 400V               | kW 21   |
|                                                                    | 500V               | kW 26   |
|                                                                    | 690V               | kW 36   |
| IEC max current $I_e$ in DC1 with L/R = 1ms with 1 poles in series | =24V               | A 20    |
|                                                                    | 48V                | A 18    |
|                                                                    | 75V                | A 18    |
|                                                                    | 110V               | A 6     |
|                                                                    | 220V               | A –     |
| IEC max current $I_e$ in DC1 with L/R = 1ms with 2 poles in series | =24V               | A 23    |
|                                                                    | 48V                | A 23    |
|                                                                    | 75V                | A 23    |
|                                                                    | 110V               | A 16    |
|                                                                    | 220V               | A 1     |
| IEC max current $I_e$ in DC1 with L/R = 1ms with 3 poles in series | =24V               | A 23    |
|                                                                    | 48V                | A 23    |
|                                                                    | 75V                | A 23    |
|                                                                    | 110V               | A 18    |

|                                                                      |          |      |     |
|----------------------------------------------------------------------|----------|------|-----|
|                                                                      | 220V     | A    | 12  |
| IEC max current Ie in DC1 with L/R = 1ms with 4 poles in series      |          |      |     |
|                                                                      | =24V     | A    | —   |
|                                                                      | 48V      | A    | —   |
|                                                                      | 75V      | A    | —   |
|                                                                      | 110V     | A    | —   |
|                                                                      | 220V     | A    | —   |
| IEC max current Ie in DC3-DC5 with L/R = 15ms with 1 poles in series |          |      |     |
|                                                                      | =24V     | A    | 15  |
|                                                                      | 48V      | A    | 13  |
|                                                                      | 75V      | A    | 13  |
|                                                                      | 110V     | A    | 2   |
|                                                                      | 220V     | A    | —   |
| IEC max current Ie in DC3-DC5 with L/R = 15ms with 2 poles in series |          |      |     |
|                                                                      | =24V     | A    | 18  |
|                                                                      | 48V      | A    | 18  |
|                                                                      | 75V      | A    | 16  |
|                                                                      | 110V     | A    | 10  |
|                                                                      | 220V     | A    | 2   |
| IEC max current Ie in DC3-DC5 with L/R = 15ms with 3 poles in series |          |      |     |
|                                                                      | =24V     | A    | 22  |
|                                                                      | 48V      | A    | 22  |
|                                                                      | 75V      | A    | 18  |
|                                                                      | 110V     | A    | 15  |
|                                                                      | 220V     | A    | 8   |
| IEC max current Ie in DC3-DC5 with L/R = 15ms with 4 poles in series |          |      |     |
|                                                                      | =24V     | A    | —   |
|                                                                      | 48V      | A    | —   |
|                                                                      | 75V      | A    | —   |
|                                                                      | 110V     | A    | —   |
|                                                                      | 220V     | A    | —   |
| Short-time allowable current for 10s (IEC/EN60947-1)                 |          | A    | 200 |
| Protection fuse                                                      |          |      |     |
|                                                                      | gG (IEC) | A    | 50  |
|                                                                      | aM (IEC) | A    | 25  |
| Making capacity (RMS value)                                          |          | A    | 250 |
| Breaking capacity at voltage                                         |          |      |     |
|                                                                      | 440V     | A    | 200 |
|                                                                      | 500V     | A    | 184 |
|                                                                      | 690V     | A    | 102 |
| Resistance per pole (average value)                                  |          | m?   | 2.5 |
| Power dissipation per pole (average value)                           |          |      |     |
|                                                                      | Ith      | W    | 2.6 |
|                                                                      | AC3      | W    | 1.6 |
| Tightening torque for terminals                                      |          |      |     |
|                                                                      | min      | Nm   | 1.5 |
|                                                                      | max      | Nm   | 1.8 |
|                                                                      | min      | lbin | 1.1 |
|                                                                      | max      | lbin | 1.5 |
| Tightening torque for coil terminal                                  |          |      |     |
|                                                                      | min      | Nm   | 0.8 |
|                                                                      | max      | Nm   | 1   |
|                                                                      | min      | lbin | 0.8 |

|                                                     |                  |                  |                       |
|-----------------------------------------------------|------------------|------------------|-----------------------|
|                                                     | max              | I <sub>bin</sub> | 0.74                  |
| Max number of wires simultaneously connectable      |                  | Nr.              | 2                     |
| Conductor section                                   |                  |                  |                       |
| AWG/Kcmil                                           | max              |                  | 10                    |
| Flexible w/o lug conductor section                  | min              | mm <sup>2</sup>  | 1                     |
|                                                     | max              | mm <sup>2</sup>  | 6                     |
| Flexible c/w lug conductor section                  | min              | mm <sup>2</sup>  | 1                     |
|                                                     | max              | mm <sup>2</sup>  | 4                     |
| Flexible with insulated spade lug conductor section | min              | mm <sup>2</sup>  | 1                     |
|                                                     | max              | mm <sup>2</sup>  | 4                     |
| Power terminal protection according to IEC/EN 60529 |                  |                  | IP20 when wired       |
| <b>Mechanical features</b>                          |                  |                  |                       |
| Operating position                                  | normal allowable |                  | Vertical plan ±30°    |
| Fixing                                              |                  |                  | Screw / DIN rail 35mm |
| Weight                                              |                  | g                | 348                   |
| Conductor section                                   |                  |                  |                       |
| AWG/kcmil conductor section                         | max              |                  | 10                    |
| <b>Auxiliary contact characteristics</b>            |                  |                  |                       |
| Thermal current I <sub>th</sub>                     |                  | A                | 10                    |
| IEC/EN 60947-5-1 designation                        |                  |                  | A600 - P600           |
| Operating current AC15                              | 230V             | A                | 3                     |
|                                                     | 400V             | A                | 1.9                   |
|                                                     | 500V             | A                | 1.4                   |
| Operating current DC12                              | 110V             | A                | 5.7                   |
| Operating current DC13                              | 24V              | A                | 5.7                   |
|                                                     | 48V              | A                | 2.9                   |
|                                                     | 60V              | A                | 2.3                   |
|                                                     | 110V             | A                | 1.25                  |
|                                                     | 125V             | A                | 1.1                   |
|                                                     | 220V             | A                | 0.55                  |
|                                                     | 600V             | A                | 0.2                   |
| <b>Operations</b>                                   |                  |                  |                       |
| Mechanical life                                     |                  | cycles           | 20000000              |
| Electrical life                                     |                  | cycles           | 1200000               |
| <b>Safety related data</b>                          |                  |                  |                       |
| Performance level B10d according to EN/ISO 13489-1  | rated load       | cycles           | 1200000               |
|                                                     | mechanical load  | cycles           | 20000000              |
| Mirror contacts according to IEC/EN 60947-4-1       |                  |                  | yes                   |
| EMC compatibility                                   |                  |                  | yes                   |
| <b>AC coil operating</b>                            |                  |                  |                       |
| Rated AC voltage at 60Hz                            |                  | V                | 220                   |

## AC operating voltage

of 60Hz coil powered at 60Hz  
pick-up

|     |     |     |
|-----|-----|-----|
| min | %Us | 80  |
| max | %Us | 110 |

drop-out

|     |     |    |
|-----|-----|----|
| min | %Us | 20 |
| max | %Us | 55 |

## AC average coil consumption at 20°C

of 60Hz coil powered at 60Hz

|         |    |    |
|---------|----|----|
| in-rush | VA | 75 |
| holding | VA | 9  |

## Dissipation at holding =20°C 50Hz

|   |     |
|---|-----|
| W | 2.5 |
|---|-----|

## Max cycles frequency

## Mechanical operation

|          |      |
|----------|------|
| cycles/h | 3600 |
|----------|------|

## Operating times

### Average time for Us control

in AC

Closing NO

|     |    |    |
|-----|----|----|
| min | ms | 8  |
| max | ms | 24 |

Opening NO

|     |    |    |
|-----|----|----|
| min | ms | 10 |
| max | ms | 20 |

Closing NC

|     |    |    |
|-----|----|----|
| min | ms | 14 |
| max | ms | 28 |

Opening NC

|     |    |    |
|-----|----|----|
| min | ms | 7  |
| max | ms | 18 |

## UL technical data

### Full-load current (FLA) for three-phase AC motor

|         |   |    |
|---------|---|----|
| at 480V | A | 21 |
| at 600V | A | 17 |

### Yielded mechanical performance

for single-phase AC motor

|          |    |   |
|----------|----|---|
| 110/120V | HP | 2 |
| 230V     | HP | 3 |

for three-phase AC motor

|          |    |     |
|----------|----|-----|
| 200/208V | HP | 7.5 |
| 220/230V | HP | 7.5 |
| 460/480V | HP | 15  |
| 575/600V | HP | 15  |

## General USE

Contactor

|            |   |    |
|------------|---|----|
| AC current | A | 32 |
|------------|---|----|

Auxiliary contacts


|            |   |     |
|------------|---|-----|
| AC voltage | V | 600 |
| AC current | A | 10  |
| DC voltage | V | 250 |
| DC current | A | 1   |

### Short-circuit protection fuse, 600V


High fault

|                       |    |     |
|-----------------------|----|-----|
| Short circuit current | kA | 100 |
|-----------------------|----|-----|

|                                                      |                       |    |             |
|------------------------------------------------------|-----------------------|----|-------------|
|                                                      | Fuse rating           | A  | 60          |
|                                                      | Fuse class            |    | J           |
| Standard fault                                       |                       |    |             |
|                                                      | Short circuit current | kA | 5           |
|                                                      | Fuse rating           | A  | 100         |
| Contact rating of auxiliary contacts according to UL |                       |    | A600 - P600 |
| Ambient conditions                                   |                       |    |             |
| Temperature                                          |                       |    |             |
|                                                      | Operating temperature |    |             |
|                                                      | min                   | °C | -50         |
|                                                      | max                   | °C | 70          |
|                                                      | Storage temperature   |    |             |
|                                                      | min                   | °C | -60         |
|                                                      | max                   | °C | 80          |
| Max altitude                                         |                       | m  | 3000        |
| Resistance & Protection                              |                       |    |             |
| Pollution degree                                     |                       |    | 3           |
| Dimensions                                           |                       |    |             |



## Wiring diagrams



## Certifications and compliance

### Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN 60947-1

IEC/EN 60947-4-1

UL 60947-1

UL 60947-4-1

### Certificates

CCC

cULus

EAC

## ETIM classification

ETIM 8.0

EC000066 -  
Power contactor,  
AC switching