



Product designation

Power contactor

Product type designation

BF26

Contact characteristics


Number of poles	Nr.	3
Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	6
Operational frequency	min	Hz 25
	max	Hz 400
IEC Conventional free air thermal current I_{th}	A	45
Operational current I_e	AC-1 (=40°C)	A 45
	AC-1 (=55°C)	A 36
	AC-1 (=70°C)	A 32
	AC-3 (=440V =55°C)	A 26
	AC-4 (400V)	A 11.5
Rated operational power AC-3 (T=55°C)	230V	kW 7.3
	400V	kW 13
	415V	kW 14
	440V	kW 14
	500V	kW 15.6
	690V	kW 18.5
Rated operational power AC-1 (T=40°C)	230V	kW 17
	400V	kW 30
	500V	kW 37
	690V	kW 51
IEC max current I_e in DC1 with L/R = 1ms with 1 poles in series	=24V	A 25
	48V	A 21
	75V	A 18
	110V	A 6
	220V	A –
IEC max current I_e in DC1 with L/R = 1ms with 2 poles in series	=24V	A 28
	48V	A 28
	75V	A 25
	110V	A 22
	220V	A 2
IEC max current I_e in DC1 with L/R = 1ms with 3 poles in series	=24V	A 28
	48V	A 28
	75V	A 25
	110V	A 24

	220V	A	20
IEC max current Ie in DC1 with L/R = 1ms with 4 poles in series			
	=24V	A	28
	48V	A	28
	75V	A	25
	110V	A	24
	220V	A	26
IEC max current Ie in DC3-DC5 with L/R = 15ms with 1 poles in series			
	=24V	A	18
	48V	A	15
	75V	A	13
	110V	A	2
	220V	A	–
IEC max current Ie in DC3-DC5 with L/R = 15ms with 2 poles in series			
	=24V	A	20
	48V	A	20
	75V	A	18
	110V	A	13
	220V	A	3
IEC max current Ie in DC3-DC5 with L/R = 15ms with 3 poles in series			
	=24V	A	25
	48V	A	25
	75V	A	20
	110V	A	18
	220V	A	19
IEC max current Ie in DC3-DC5 with L/R = 15ms with 4 poles in series			
	=24V	A	30
	48V	A	30
	75V	A	25
	110V	A	20
	220V	A	15
Short-time allowable current for 10s (IEC/EN60947-1)		A	210
Protection fuse			
	gG (IEC)	A	50
	aM (IEC)	A	32
Making capacity (RMS value)		A	260
Breaking capacity at voltage			
	440V	A	208
	500V	A	184
	690V	A	168
Resistance per pole (average value)		m?	2
Power dissipation per pole (average value)			
	Ith	W	4
	AC3	W	1.4
Tightening torque for terminals			
	min	Nm	2.5
	max	Nm	3
	min	lbin	1.8
	max	lbin	2.2
Tightening torque for coil terminal			
	min	Nm	0.8
	max	Nm	1
	min	lbin	0.8


		max	I _{bin}	0.74
Max number of wires simultaneously connectable			Nr.	2
Conductor section	AWG/Kcmil	max		6
Flexible w/o lug conductor section		min	mm ²	2.5
		max	mm ²	16
Flexible c/w lug conductor section		min	mm ²	1
		max	mm ²	10
Flexible with insulated spade lug conductor section		min	mm ²	1
		max	mm ²	10
Power terminal protection according to IEC/EN 60529				IP20 when wired
Mechanical features				
Operating position		normal allowable		Vertical plan ±30°
Fixing				Screw / DIN rail 35mm
Weight			g	436
Conductor section	AWG/kcmil conductor section	max		6
Operations				
Mechanical life			cycles	20000000
Electrical life			cycles	1600000
Safety related data				
Performance level B10d according to EN/ISO 13489-1		rated load mechanical load	cycles	1600000
			cycles	20000000
Mirror contacts according to IEC/EN 60947-4-1				yes
EMC compatibility				yes
AC coil operating				
Rated AC voltage at 50/60Hz			V	400
AC operating voltage	of 50/60Hz coil powered at 50Hz			
	pick-up	min	%U _s	80
		max	%U _s	110
	drop-out	min	%U _s	20
		max	%U _s	55
	of 50/60Hz coil powered at 60Hz			
	pick-up	min	%U _s	85
		max	%U _s	110
	drop-out	min	%U _s	20
		max	%U _s	55
AC average coil consumption at 20°C	of 50/60Hz coil powered at 50Hz			

		in-rush holding	VA VA	75 9
of 50/60Hz coil powered at 60Hz				
		in-rush holding	VA VA	70 6.5
of 60Hz coil powered at 60Hz				
		in-rush holding	VA VA	75 9
Dissipation at holding =20°C 50Hz			W	2.5
Max cycles frequency				
Mechanical operation			cycles/h	3600
Operating times				
Average time for Us control in AC				
Closing NO		min	ms	8
		max	ms	24
Opening NO		min	ms	5
		max	ms	15
Closing NC		min	ms	9
		max	ms	20
Opening NC		min	ms	9
		max	ms	17
UL technical data				
Full-load current (FLA) for three-phase AC motor		at 480V	A	21
		at 600V	A	22
Yielded mechanical performance for single-phase AC motor		110/120V	HP	2
		230V	HP	5
for three-phase AC motor		200/208V	HP	7.5
		220/230V	HP	7.5
		460/480V	HP	15
		575/600V	HP	20
General USE				
Contactor		AC current	A	45
Short-circuit protection fuse, 600V High fault		Short circuit current	kA	100
		Fuse rating	A	100
		Fuse class	J	
Standard fault		Short circuit current	kA	5
		Fuse rating	A	100
Ambient conditions				
Temperature				
Operating temperature		min	°C	-50

Storage temperature	max	°C	70
	min	°C	-60
	max	°C	80
Max altitude		m	3000
Resistance & Protection			
Pollution degree			3
Dimensions			



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN 60947-1

IEC/EN 60947-4-1

UL 60947-1

UL 60947-4-1

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000066 -
Power contactor,
AC switching