

Dissipation at holding =20°C 50Hz		holding	VA	1.5...3.7
			W	1...2.5
DC coil operating				
DC rated control voltage				
		min	V	20
		max	V	48
DC rated control voltage			V	24
DC operating voltage				
pick-up		min	%Us	85 Us min
		max	%Us	110 Us max
drop-out				
		max	%Us	=70 Us min
Average coil consumption =20°C				
		in-rush	W	23...68
		holding	W	1.2...1,9
Max cycles frequency				
Mechanical operation			cycles/h	1500
Operating times				
Average time for Us control				
in AC	Closing NO	min	ms	12
		max	ms	28
	Opening NO	min	ms	8
		max	ms	22
in DC				
	Closing NO	min	ms	40
		max	ms	85
	Opening NO	min	ms	20
		max	ms	55
UL technical data				
Full-load current (FLA) for three-phase AC motor				
		at 480V	A	52
		at 600V	A	41
Yielded mechanical performance				
for single-phase AC motor		110/120V	HP	5
		230V	HP	10
for three-phase AC motor		200/208V	HP	15
		220/230V	HP	20
		460/480V	HP	40
		575/600V	HP	40
General USE				
Contactor				
	AC current	A	90	
Short-circuit protection fuse, 600V				
High fault				
	Short circuit current	kA	100	
	Fuse rating	A	150	

	Fuse class	J
Standard fault		
	Short circuit current	kA 5
	Fuse rating	A 150
	Fuse class	RK5

[illegible][illegible]


Operating temperature	min	°C	-40
	max	°C	70

Storage temperature

min	°C	-50
max	°C	80

Max altitude[illegible]

Resistance & Protection

[illegible]3[illegible]

Wiring diagrams

