





Product designation			Adjustable roller lever	
Product type designation			KBF	
General characteristics				
Material			Housing	Polymer thermoplastic
			Roller	Plastic
Contact characteristics				
Type of contact			2NC Snap action	
Thermal current Ith			A	10
IEC/EN 60947-5-1 designation			A600 Q300	
Rated insulation voltage Ui			V	690
Rated impulse withstand voltage Uimp			kV	6
Insulation class			II	
Short-circuit protection with fuse			Class/A	10 gG/SC QUICK FUSE
Switching speed			min	m/s
			max	m/s
IEC Conventional free air thermal current Ith			A	10
Resistance per pole (average value)			m?	<10
Mechanical features				
Operating head fixing			Locking bayonet insert	
Operating torque			Ncm	3
			ozin	4.25
Tightening torque (Max)				
Switch fixing			Nm	2.5
			lbin	22.1
Contact terminals			Nm	0.8
			lbin	7
Body lid screw fixing			Nm	0.8
			lbin	7
Conductor section				
AWG/Kcmil			min	16
			max	14
IEC			min	mm²
			max	mm²

Cable connection			Self-releasing screw terminal		
Cable entry			M20 on the bottom		
Operations					
Mechanical life			cycles	<10000000	
Mechanical operation			cycles/h	3600	
Ambient conditions					
Temperature					
Operating temperature			min	°C	-25
			max	°C	+70
Storage temperature			min	°C	-40
			max	°C	+70
Resistance & Protection					
IP degree			Terminals	IP20	
			Body housing	IP65	
Pollution degree			3		
Dimensions					



Wiring diagrams

Snap action



Certifications and compliance

Compliance

CSA C22.2 n° 14
EN 50047
IEC/EN 60204-1
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508

Certificates

CCC
cULus
EAC

ETIM classification

ETIM 8.0

EC000030 - End
switch