



Wobble stick,
omnidirectional
KNM

Product designation

Product type designation

General characteristics

Material

Housing

Aluminium-zinc
alloy
Semirigid

Rod

Contact characteristics

Type of contact

1NO+1NC Slow
action make
before break

Thermal current Ith

A

10

IEC/EN 60947-5-1 designation

A300 Q300

Rated insulation voltage Ui

V

440

Rated impulse withstand voltage Uimp

kV

4

Short-circuit protection with fuse

Class/A

10 gG/SC
QUICK FUSE

Switching speed

min

m/s

0.5

max

m/s

1.5

IEC Conventional free air thermal current Ith

A

10

Resistance per pole (average value)

m?

<10

Mechanical features

Operating head fixing

Locking bayonet
insert

Operating torque

Ncm

1

ozin

1.42

Tightening torque (Max)

Switch fixing

Nm

2.5

lbin

22.1

Contact terminals

Nm

0.8

lbin

7

Body lid screw fixing

Nm

0.8

lbin

7

Conductor section

AWG/Kcmil

min

16

max

14

IEC

min

mm²


1or 2

max

mm²


2.5

Cable connection				Self-releasing screw terminal
Cable entry				M20 on the sides
Operations				
Mechanical life				cycles <10000000
Mechanical operation				cycles/h 3600
Ambient conditions				
Temperature				
Operating temperature				
				min °C -25
				max °C +70
Storage temperature				
				min °C -40
				max °C +70
Resistance & Protection				
IP degree				
Terminals				IP20
Body housing				IP65
Pollution degree				3
Dimensions				



Wiring diagrams

Slow action



1NO + 1NC
make before break

Certifications and compliance

Compliance

CSA C22.2 n° 14

EN 50047

IEC/EN 60204-1

IEC/EN 60947-1

IEC/EN 60947-5-1

UL508

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000030 - End
switch