

Product designation	Two pedal, with safety lever on both pedals - both with cover				
Product type designation	KRD001				
General characteristics					
Material	Housing	Aluminium-zinc alloy			
Contact characteristics					
Type of contact	1NO+1NC Snap action				
Thermal current I_{th}	A	10			
IEC/EN 60947-5-1 designation	A300 Q300				
Rated insulation voltage U_i	V	440			
Rated impulse withstand voltage U_{imp}	kV	4			
Short-circuit protection with fuse	Class/A	10 gG fuse			
IEC Conventional free air thermal current I_{th}	A	10			
Resistance per pole (average value)	m?	<10			
Mechanical features					
Tightening torque (Max)	Contact terminals				
		Nm	1		
		lbin	0.74lbft		
Cable connection	Self-releasing screw terminal				
Cable entry	1 x M20				
Operations					
Mechanical life	cycles >10000000				
Ambient conditions					
Temperature	Operating temperature				
		min	°C -25		
		max	°C +70		
	Storage temperature				
		min	°C -40		
		max	°C +70		
Resistance & Protection					
IP degree	Terminals	IP20			
	Body housing	IP54			
Pollution degree	3				
Certifications and compliance					
Compliance	EN 60447.				
	IEC/EN 60204-1				
	IEC/EN 60947-1				
	IEC/EN 60947-5-1				
Certificates	EAC				
ETIM classification					
ETIM 8.0	EC001258 - Foot switch				