



Product designation

Roller centre  
push lever

Product type designation

KSC3

### General characteristics

Material

Housing

Polymer  
thermoplastic

### Contact characteristics

Type of contact

1NO/NC

Thermal current Ith

A

15

IEC/EN 60947-5-1 designation

A600 P300

Rated insulation voltage Ui

V

250

Switching speed

min

m/s

0.01

max

m/s

1

Operating speed

min

m/s

0.05

max

m/s

1

IEC Conventional free air thermal current Ith

A

15

Resistance per pole (average value)

m?

<15

Conductivity

10mA 5V

### Mechanical features

Terminals type

Faston

Operating head fixing

Fixed

Operating torque

N

1.5

ozin

5.4

Weight

g

38

### Operations

Mechanical life

cycles

20000000

Electrical life

cycles

500000

Mechanical operation

cycles/h

240

### Ambient conditions

Temperature

Operating temperature

min

°C

-25

max

°C

+70

Storage temperature

min

°C

-40

max

°C

+70

### Resistance & Protection

IP degree


Body housing

IP00 or IP20 with  
terminal shroud


Pollution degree

3

## Dimensions



## Wiring diagrams



## Certifications and compliance

### Compliance

CSA C22.2 n° 14.

IEC/EN 60947-1

IEC/EN 60947-5-1

IEC/EN 61058-1

UL508

### Certificates

cURus

EAC

## ETIM classification

ETIM 8.0

EC000030 - End  
switch