





Product designation	Roller centre push lever					
Product type designation	KSC9					
<b>General characteristics</b>						
Material						
	Housing	Polymer thermoplastic				
<b>Contact characteristics</b>						
Type of contact	1NO/NC					
Thermal current $I_{th}$	A	15				
IEC/EN 60947-5-1 designation	A600 P300					
Rated insulation voltage $U_i$	V	250				
Switching speed	min	m/s	0.01			
	max	m/s	1			
Operating speed	min	m/s	0.05			
	max	m/s	1			
IEC Conventional free air thermal current $I_{th}$	A	15				
Resistance per pole (average value)	m?	<15				
Conductivity	10mA 5V					
<b>Mechanical features</b>						
Terminals type	Faston					
Operating head fixing	Fixed					
Operating torque	N	1.7				
	ozin	6.1				
Weight	g	39				
<b>Operations</b>						
Mechanical life	cycles	20000000				
Electrical life	cycles	500000				
Mechanical operation	cycles/h	240				
<b>Ambient conditions</b>						
Temperature	Operating temperature					
	min	°C	-25			
	max	°C	+70			
Storage temperature	min	°C	-40			
	max	°C	+70			
<b>Resistance &amp; Protection</b>						
IP degree	Body housing		IP00 or IP20 with terminal shroud			
Pollution degree	3					

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14.

IEC/EN 60947-1

IEC/EN 60947-5-1

IEC/EN 61058-1

UL508

Certificates

cURus

EAC

ETIM classification

ETIM 8.0

EC000030 - End switch