
## PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES CHROMED PLASTIC, FLUSH, START/GREEN



Product designation				Pushbutton actuators, spring return, with symbol
Product type designation				LPCB11
General characteristic	S			0
Colour				Green
Type of positions				Flush
Material				Polyamide
IEC degree of protection				IP66, IP67 and IP69K
Mechanical features				
Operating force			kg-lb	<0.5Kg / 1.1lb
Mechanical life			cycles	5000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120
Weight			g	25
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+85
Dimensions				



## Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1



## **LPCB1163**

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES CHROMED PLASTIC, FLUSH, START/GREEN

	UL508	
Certificates		
	CCC	
	cULus	
	EAC	
	RINA	
ETIM classification		

ETIM 8.0

EC000221 -Front element for push button