PUSHBUTTON ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES CHROMED PLASTIC, EXTENDED, BLACK



| Product designation | | | Pushbutton actuator, spring return |
|---|-----|--------|--|
| Product type designation | | | LPCB20 |
| General characteristics | | | |
| Colour | | | Black |
| Type of positions | | | Extended |
| Material | | | Polyamide |
| IEC degree of protection | | | IP66, IP67 and IP69K |
| Mechanical features | | | |
| Operating force | | kg-lb | <0.5Kg / 1.1lb |
| Mechanical life - spring return actuators | | cycles | 5000000 |
| Fixing | | | Without mounting adapter |
| Mounting adapter | | | LPXAU120 |
| Weight | | g | 27 |
| UL technical data | | | |
| UL degree of protection | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | |
| Temperature | | | |
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +70 |
| Storage temperature | | | |
| | min | °C | -40 |
| | max | °C | +85 |
| Dimensions | | | |

16.7 (0.66") (0.89.5 (1.16")

Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508



LPCB202

PUSHBUTTON ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES CHROMED PLASTIC, EXTENDED, BLACK

| Certificates | | - | |
|--------------|-------|---|--|
| | CCC | | |
| | cULus | | |
| | EAC | | |
| | RINA | | |

ETIM classification

ETIM 8.0

EC000221 -Front element for push button