



Product designation

LED integrated monoblock pilot lights steady light LPM

Product type designation

General characteristics

Colour

Orange

Material

Polyamide

IEC degree of protection

IP66, IP67 and IP69K on front; IP20 on rear

Electrical characteristics

Rated frequency

Hz 50-60

Supply voltage (AC)

V 12 (-15% ... +10% Ue)

Supply voltage (DC)

V 12 (-15% ... +10% Ue)

Operations

Electrical life

hours >30000

Mechanical features

Tightening torque for terminals max

Nm 0.8

Terminals screw

Screw termination

Conductor section

AWG/kcmil conductor section

min	18
max	16

IEC

max	mm ² 2.5
-----	---------------------

Fixing

Ring fixing Ø22mm

Weight

g 21

UL technical data

UL degree of protection

Type1, 2, 3R, 4, 4X, 12, 12K on front


Ambient conditions

Temperature


Operating temperature

min	°C -25
max	°C +70

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

[CSA C22.2 n° 14](#)

[IEC/EN/BS 60947-1](#)

[IEC/EN/BS 60947-5-1](#)

[UL508](#)

Certificates

[cULus](#)

[EAC](#)

ETIM classification

ETIM 8.0

EC000272 -
Indicator light
complete