



Product designation

LED integrated  
monoblock pilot  
lights steady light  
LPML

Product type designation

General characteristics

Colour

Transparent

Material

Polyamide

IEC degree of protection

IP66, IP67 and  
IP69K on front;  
IP20 on rear

Electrical characteristics

Rated frequency

Hz 50-60

Supply voltage (AC)

V 380...415 (-15%  
... +10% Ue)

Operations

Electrical life

hours >30000

Mechanical features

Tightening torque for terminals max

Nm 0.8

Conductor section

AWG/kcmil conductor section

min	18
max	16

IEC

min	mm <sup>2</sup>	0.5
max	mm <sup>2</sup>	2.5

Weight

g 24

UL technical data

UL degree of protection

Type1, 2, 3R, 4,  
4X, 12, 12K on  
front


Ambient conditions

Temperature


Operating temperature

min	°C	-25
max	°C	+70

Dimensions



**Wiring diagrams**



**Certifications and compliance**

**Compliance**

[CSA C22.2 n° 14](#)

[IEC/EN/BS 60947-1](#)

[IEC/EN/BS 60947-5-1](#)

[UL508](#)

**Certificates**

[cULus](#)

[EAC](#)

**ETIM classification**

**ETIM 8.0**

EC000272 -  
Indicator light  
complete