



Product designation	Push-push button actuators																		
Product type designation	LPSQ10																		
General characteristics																			
Colour	Yellow																		
Type of positions	Flush. Push on-push off																		
Material	Aluminium and zinc alloy																		
IEC degree of protection	IP66, IP67 and IP69K																		
Mechanical features																			
Operating force	kg-lb	<0.5Kg / 1.1lb																	
Mechanical life - Push-Push actuators	cycles	500000																	
Fixing	Without mounting adapter																		
Mounting adapter	LPXAU120M																		
UL technical data																			
UL degree of protection	Type1, 2, 3R, 4, 4X, 12, 12K																		
Ambient conditions																			
Temperature	<table> <tr> <td>Operating temperature</td> <td>min</td> <td>°C</td> <td>-25</td> </tr> <tr> <td></td> <td>max</td> <td>°C</td> <td>+70</td> </tr> </table> <table> <tr> <td>Storage temperature</td> <td>min</td> <td>°C</td> <td>-40</td> </tr> <tr> <td></td> <td>max</td> <td>°C</td> <td>+85</td> </tr> </table>			Operating temperature	min	°C	-25		max	°C	+70	Storage temperature	min	°C	-40		max	°C	+85
Operating temperature	min	°C	-25																
	max	°C	+70																
Storage temperature	min	°C	-40																
	max	°C	+85																
Dimensions																			
Certifications and compliance																			
Compliance	<ul style="list-style-type: none"> CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508 																		
Certificates	cULus																		
ETIM classification																			
ETIM 8.0	EC000029 - Push-switch button																		

