
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES METAL, 3 POSITION, 1 - 0 - 2. WITHDRAL AT 1 OR 0 OR 2



Product designation				Selector switch actuator key - 3 position
Product type designate	tion			LPSS33
General characteristic	es S			
Colour				Black
Type of positions				1 - 0 - 2, key extraction in 1 and 0 and 2
Material				Aluminium and zinc alloy
IEC degree of protect	tion			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
	-	max	°C	+70
	Storage temperature		2.0	40
		min	°C	-40
Dimensions		max	C	+85
Dimensions				



Certifications and compliance

\sim	
1 . Ow	กมากกก
COULT	pliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

Certificates

cULus

ETIM classification





ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES METAL, 3 POSITION, 1 - 0 - 2. WITHDRAL AT 1 OR 0 OR 2

ETIM 8.0

EC002611 -Control switch