



Illuminated  
selector switch  
actuator - 3  
position  
LPSSL13

Product designation

Product type designation

#### General characteristics

|                          |                          |
|--------------------------|--------------------------|
| Colour                   | Green                    |
| Type of positions        | 1 - 0 - 2                |
| Material                 | Aluminium and zinc alloy |
| IEC degree of protection | IP66, IP67 and IP69K     |

#### Mechanical features

|                  |        |                          |
|------------------|--------|--------------------------|
| Mechanical life  | cycles | 1000000                  |
| Fixing           |        | Without mounting adapter |
| Mounting adapter |        | LPXAU120M                |

#### UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

#### Ambient conditions

Temperature


Operating temperature

|     |    |     |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +70 |

Storage temperature

|     |    |     |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +85 |

#### Dimensions



#### Certifications and compliance

Compliance

|                     |
|---------------------|
| CSA C22.2 n° 14     |
| IEC/EN/BS 60947-1   |
| IEC/EN/BS 60947-5-1 |
| UL508               |

Certificates

cULus

#### ETIM classification

ETIM 8.0

EC002611 -  
Control switch