



Product designation		Variable speed drives	
Product type designation		VLB3	
General characteristics			
Rated power supply voltage		400...480VAC 50/60Hz	
Rated output voltage		VAC	Three-phase 0... 480VAC 0-599Hz
Rated output current		A	212
Rated output power		kW	110
Rated output power		HP	150 (Heavy load) / 175 (Standard load)
EMC filter		Built-in EMC suppressor cat. C2	
Technical features			
Input type		Three-phase	
Rated mains voltage		VAC	400...480
Operating mains voltage range		VAC	340...528
Rated mains frequency		Hz	50/60
Operating mains frequency range		Hz	45...65
Rated mains current with mains choke		198 (heavy load) / 234 (standard load)	
Output type		Three-phase	
Output voltage range		VAC	0...480
Output frequency range		Hz	0...599
Current overload		%/s	150% for 60s; 200% for 3s
Apparent output power		142 (heavy load) / 171 (standard load)	
Power loss		4kHz: 2305W (heavy load) / 2760 (standard load)	
Brake chopper		Yes	
Switching frequency		2...16kHz	
Max motor cable length			
Shielded		Without EMC category	m 200
		Category C1	m 3
		Category C2	m 20
		Category C3	m 100
Unshielded			


Without EMC category m 200

Functions

Motor control modes	V/f linear, quadratic torque, sensorless vector control, ECO mode, servo control with encoder feedback, multipoint V/f curve, V/f closed loop control with encoder feedback, torque setpoint, sensorless
Speed reference signals	External potentiometer 0...10kΩ Voltage signals: 0...10VDC or -10...+10VDC Current signals: 0/4...20mA Buttons on front keyboard Door-mount installation kit 15 preset speeds via digital inputs Motor potentiometer
3-wire control	Yes
S-shape curves	Yes
Slip compensation	Yes
Flying restart	Yes
Access to DC bus	Yes
DC braking	Yes
DC injection at start	Yes
PID control	Yes, with sleep and rinse function
Sequencer (programmable frequency/time cycles)	Yes
Preset speeds	Yes
Motorpotentiometer	Yes
Different parameter configuration sets	Yes
Parameters changeover function	Yes
Favorite parameters menu	Yes
Autotuning	No
Safe torque Off (STO) safety function	Optional
PTC probe input	Yes


Protections	Overcurrent Output short circuit and earth/ground leakage Overvoltage Undervoltage Phase loss Motor heat overload (i2t) Overspeed Speed reverse
Special funct.	Multi-pump PID control (1 main pump frequency regulated + 2 auxiliary pumps activated in direct mode in case of necessity)
Input and Output	
Number of digital input	Nr. 5
Digital input type	Selectable PNP or NPN logic
Number of digital output	Nr. 2
Digital output arrangement	1 relay output with changeover contact (C/O-SPDT) + 1 digital output
Output contacts ratings	Relay output: 3A 250VAC Digital output: 100mA max 30VDC
Number of analog input	Nr. 2
Analog input type	Configurable 0/2...10VDC, -10...+10VDC, 0...5VDC, 0/4...20mA
Number of analog output	Nr. 1
Analog output type	configurable as 0...10VDC, 0...5VDC, 2...10VDC, 0/4...20mA
Ambient conditions	
Temperature	
Operating temperature	
	min °C -10
	max °C +55

		Current derating	switching frequency 2 or 4kHz: 2.5%/°C over 45°C switching frequency 8 or 16kHz: 2.5%/°C over 40°C
Storage temperature			
		min	°C
		max	°C
			-25
			+60
Relative humidity			%
			5...95% (with no condensing)
Max altitude			m
			4000m (over 1000m derate the rated current by 5%/1000m)
Maximum Pollution degree			2
Overvoltage category			III up to 2000m altitude (II above 2000m)
Housing			
Installation position			Vertical
IP degree of protection			IP20
Dimensions (W x H x D)		mm	258 x 775 x 304
Weight		Kg	35.6
Dimensions			



TYPE	A	B	C	D
VLB3 0150 A480	204.5 (8.05")	366 (14.41")	222 (8.74")	347 (13.66")
VLB3 0185 A480	204.5 (8.05")	366 (14.41")	222 (8.74")	347 (13.66")
VLB3 0220 A480	204.5 (8.05")	366 (14.41")	222 (8.74")	347 (13.66")
VLB3 0300 A480	250 (9.84")	520 (20.47")	230 (9.05")	450 (17.72")
VLB3 0370 A480	250 (9.84")	520 (20.47")	230 (9.05")	450 (17.72")
VLB3 0450 A480	250 (9.84")	520 (20.47")	230 (9.05")	450 (17.72")
VLB3 0550 A480	250 (9.84")	623 (24.53")	265 (10.43")	536 (21.10")
VLB3 0750 A480	250 (9.84")	623 (24.53")	265 (10.43")	536 (21.10")
VLB3 0900 A480	258 (10.16")	775 (30.51")	304 (11.97")	685 (26.97")
VLB3 1100 A480	258 (10.16")	775 (30.51")	304 (11.97")	685 (26.97")

Wiring diagrams



Compliance

EN 61800-5-1

UL61800-5-1

CSA

cULus

EAC

RCM

EC001857 -
Frequency
converter ≤ 1 kV

ETIM 8.0