




Product designation		Variable speed drives
Product type designation		VT107A240
General characteristics		
Rated power supply voltage		200...240VAC 50/60Hz
Rated output voltage	VAC	Three-phase 0...240VAC 0-599Hz
Rated output current	A	4.3
Rated output power	kW	0.75
Rated output power	HP	1
EMC filter		Built-in EMC suppressor cat. C2
Communication port		RS485, Modbus-RTU and BACnet
Technical features		
Input type		Single-phase
Rated mains voltage	VAC	200...240
Operating mains voltage range	VAC	170...264
Rated mains frequency	Hz	50/60
Rated mains current without mains choke		11
Output type		Three-phase
Output voltage range	VAC	0...240
Output frequency range	Hz	0...599
Current overload	%/s	150% for 60s
Apparent output power		1.65
Brake chopper		No
Cooling System		Natural
Switching frequency		1...16kHz
Functions		
Motor control modes		V/f linear, V/f quadratic, V/f multi-point , sensorless vector control

Speed reference signals	Frontal potentiometer External potentiometer 1...10kΩ Voltage signals: 0...10VDC Current signals: 0/4...20mA Buttons on front keyboard Door-mount keyboard 7 preset speeds via digital inputs RS485 port	
3-wire control	Yes	
S-shape curves	Yes	
Slip compensation	Yes	
Flying restart	No	
Access to DC bus	No	
DC braking	Yes	
DC injection at start	Yes	
PID control	Yes	
Sequencer (programmable frequency/time cycles)	Yes	
Preset speeds	Yes	
Motorpotentiometer	Yes	
Different parameter configuration sets	Main/alternative run command select Main/alternative frequency command select	
Parameters changeover function	No	
Favorite parameters menu	No	
Autotuning	Yes	
Safe torque Off (STO) safety function	No	
PTC probe input	Yes	
Protections	Motor overload Drive overload Overvoltage Undervoltage Phase loss Overtemperature Overspeed	
Special funct.	Multi-pump PID for the control of up to 4 VT1...drives in master-slave configuration	
Input and Output		
Number of digital input	Nr.	5
Digital input type	PNP logic	
Number of digital output	Nr.	1
Digital output arrangement	1 relay output with NO contact	

Output contacts ratings		1A 250VAC, 1A 30VDC
Number of analog input	Nr.	2
Analog input type		1 voltage analog input 0...10VDC 1 current analog input 0/4...20mA
Number of analog output	Nr.	1
Analog output type		0...10VDC
Ambient conditions		
Temperature		
Operating temperature		
	min	°C -10
	max	°C +50
Current derating		from 40 to 50°C with derating of the output current of 6%/°C
Storage temperature		
	min	°C -20
	max	°C +60
Relative humidity	%	<95
Max altitude	m	3000m (over 1000m derate the rated current by 2%/100m)
Maximum Pollution degree		2
Housing		
Installation position		Vertical
IP degree of protection		IP20
Dimensions (W x H x D)	mm	72 x 141 x 141
Weight	Kg	1

Dimensions



Certifications and compliance

Compliance

CSA 22.2 No. 274

EN 61800-5-1

UL508C

Certificates

VARIABLE SPEED DRIVE, VT1 TYPE, SINGLE-PHASE, SUPPLY 200...240VAC (50/60HZ).
BUILT-IN RS485 COMMUNICATION PORT. BUILT-IN EMC SUPPRESSOR, CAT. C2, 0.75KW

cULus

EAC

RCM

ETIM classification

ETIM 8.0

EC001857 -
Frequency
converter =< 1 kV