

PUSHBUTTONS AND SELECTOR SWITCHES SERIES **PL**atinum

Quality touch!



 **Lovato**
electric

ENERGY AND AUTOMATION

● Pushbuttons and selector switches Ø22mm



Quality touch!



● LOW ACTUATOR PROFILE

The external actuator bezel has a low profile and reduced front thickness.

● HIGH DEGREE OF PROTECTION

The actuators have been tested to guarantee a degree of protection per IEC/EN IP66, IP67, IP69K and UL Type 4X, appropriate for use even in extreme ambient conditions.

● QUICK AND EASY ACTUATOR INSTALLATION

● CUSTOMISING CAPABILITY

To simplify stock management, the series includes actuators without cap or lens and separate caps and lenses for quick installation or replacement on spring return and push-push types; all these are sold as accessories.



- Actuator fixing on the mounting surface, is obtained using its **threaded ring**, easily rotated by hand or by socket spanner/wrench.



- There is an **anti-rotation fastener** which collapses inside the gasket to allow fitting also when drilled holes are round without reference index.
- The sealing gasket for the actuator mounting surface has a gripping action (suction effect) offering additional **adhesion properties**.



- The mounting adapter and actuators each have **clearly visible reference** indications making the snap-on fitting between the two easy and intuitive.



- Electrical contact and LED elements are **snapped onto** the mounting adapter.
- The activation of the middle contacts is standard supplied on all non-illuminated spring return and push-push button or selector switch actuators.

Pushbuttons, spring return

FLUSH



LPC B10

2 ■
3 ■
4 ■
5 ■
6 ■
8 □

EXTENDED



LPC B20

2 ■
3 ■
4 ■
5 ■
6 ■
8 □

SHROUDED



LPC B30

2 ■
3 ■
4 ■
5 ■
6 ■
8 □

Pushbuttons, spring return, with symbol

NOTE: other different symbols are available also for illuminated types.

FLUSH



LPC B11

0 02 ■
04 ■
I 13 ■
18 □
II 23 ■
28 □

LPC B11

STOP 32 ■
34 ■
← 42 ■
48 □
↑ 52 ■
58 □

LPC B11

START 63 ■
68 □
R 76 ■
78 □
RESET 96 ■

EXTENDED



LPC B21

0 02 ■
04 ■
STOP 32 ■
34 ■

Illuminated buttons, spring return

FLUSH



LPC BL10

3 ■
4 ■
5 ■
6 ■
7 □ transp.

EXTENDED



LPC BL20

3 ■
4 ■
5 ■
6 ■
7 □ transp.

Mechanical reset buttons, spring return

FLUSH



LPC R100

2 ■
3 ■
4 ■
6 ■

FLUSH WITH SYMBOL



RESET LPC R1196 ■

EXTENDED



LPC R2004 ■

NOTE: contact elements can be mounted.

Push-push buttons

FLUSH



LPC Q10

2 ■
3 ■
4 ■
5 ■
6 ■
8 □

EXTENDED



LPC Q20

2 ■
3 ■
4 ■
5 ■
6 ■
8 □

Illuminated push-push buttons

FLUSH



LPC QL10

3 ■
4 ■
5 ■
6 ■
7 □ transp.

EXTENDED



LPC QL20

3 ■
4 ■
5 ■
6 ■
7 □ transp.

Pilot light heads



LPL

3 ■
4 ■
5 ■
6 ■
7 □ transp.
⚡1187 □ transp.

(symbol indicating dangerous voltage)

Contact elements



LPC E

NO 1.3 10
1.4
NC 1.1 01
1.2



LPC C

NO 1.3 10
1.4
NC 1.1 01
1.2
EM 1.7 10A
1.8 Early make
LB 1.5 01D
1.6 Late break



LPC CS

NO 1.3 10
1.4
NC 1.1 01
1.2
EM 1.7 10A
1.8 Early make



LPC CF

NO 1.3 10
1.4
NC 1.1 01
1.2

MOUNTING: Frontal
TERMINATION: Screw
MOUNTING ADAPTER: With

Frontal
Screw
Without

Frontal
Spring (push-in technology)
Without

Frontal
Faston
Without

Mounting adapter



LPC AU120

Mounting adapter for contact and LED elements with actuators. Allows mounting also on control station cover.

Mushroom head buttons

FOR EMERGENCY STOPPING ISO 13850 COMPLIANT.

Ø30mm. Turn to release.



LPC B6634 ■

Ø40mm. Turn to release.



LPC B6644 ■

FOR NORMAL STOPPING.

Ø40mm. Turn to release.



LPC B634
2 ■
4 ■

Ø40mm. Pull to release.



LPC B6744 ■

Ø40mm. Pull to release.



LPC B6742 ■

Version with Ronis keys

Types available with 5 different key codes; add "R" suffix to order code and complete with numeric code from the following: 421E, 458A, 520E, 3131A or 3433E.



Ø40mm. Turn key to release.



LPC B6844 ■ Ⓡ

Ø40mm. Turn key to release.




LPC B6842 ■ Ⓡ

Auto-monitor


Screw termination. Without mounting adapter. Auto-monitor contact elements for non-illuminated latch mushroom-head pushbuttons.



LPX C01SM



LPX C02SM



Mushroom head buttons, spring return

Ø40mm LPC B614

- 2 ■
- 3 ■
- 4 ■
- 5 ■
- 6 ■



Ø60mm LPC B616

- 2 ■
- 3 ■
- 4 ■
- 5 ■
- 6 ■



Illuminated mushroom head buttons, turn to release

Ø40mm. For emergency stopping, ISO 13850 compliant.

LPC BL6644 ■



Ø40mm. For normal stopping.

LPC BL614

- 3 ■
- 5 ■
- 6 ■



Illuminated mushroom head buttons, spring return

Ø40mm

LPC BL614

- 3 ■
- 4 ■
- 5 ■
- 6 ■
- 8 □



Plastic control stations without actuators



LPZ P

- 1A5 ■ for 1 actuator
- 1A8 □ for 1 actuator
- 2A5 ■ for 2 actuators
- 2A8 □ for 2 actuators
- 3A8 □ for 3 actuators

LPZ P

- 4A8 □ for 4 actuators
- 5A8 □ for 5 actuators
- 6A8 □ for 6 actuators

Metal control stations without actuators



LPZ M

- 1A5 ■ for 1 actuator
- 1A5P ■ for 1 actuator shrouded
- 1A8 □ for 1 actuator
- 2A5 ■ for 2 actuators
- 2A8 □ for 2 actuators

LPZ M

- 3A8 □ for 3 actuators
- 4A8 □ for 4 actuators
- 5A8 □ for 5 actuators
- 6A8 □ for 6 actuators

Plastic control stations with one actuator

Grey cover



LPZ P1 B8 01
(with one actuator
LPC B6744)

LPZ P1 B8 02
(with one actuator
LPC B344)

Yellow cover



LPZ P1 B5 02
(with one actuator
LPC B6344)

LPZ P1 B5 03
(with one actuator
LPC B6644)

Contact and LED elements for plastic control stations

Screw termination. Direct snap-in mounting on LPZ plastic control station base.

CONTACT ELEMENTS w/o mounting adapter

LED ELEMENTS, STEADY LIGHT w/o mounting adapter



LPX CB10



LPX CB01



LPX LPB

- Voltage ↑ ↑ Colour
- 12-30VAC/DC B 3 ■
 - 85-140VAC E 4 ■
 - 185-265VAC M 5 ■
 - 6 ■
 - 8 □

Total protection against overvoltages and stray currents in wiring, to reduce flickering phenomenon and withstand vibrations

LED elements



LPX LF

- Voltage ↑ ↑ Colour
- 18-30VAC/DC B 3 ■
 - 85-140VAC E 4 ■
 - 185-265VAC M 5 ■
 - 6 ■
 - 8 □



LPX LP

- Voltage ↑ ↑ Colour
- 12-30VAC/DC B 3 ■
 - 85-140VAC E 4 ■
 - 185-265VAC M 5 ■
 - 6 ■
 - 8 □



LPX LPS

- Voltage ↑ ↑ Colour
- 12-30VAC/DC B 3 ■
 - 85-140VAC E 4 ■
 - 185-265VAC M 5 ■
 - 6 ■
 - 8 □



LPX LE

- Voltage ↑ ↑ Colour
- 12-30VAC/DC B 3 ■
 - 85-140VAC/DC E 4 ■
 - 185-265VAC/DC M 5 ■
 - 6 ■
 - 8 □

MOUNTING: Frontal

Frontal

Frontal

Frontal

TERMINATION: Screw

Screw

Spring

Screw

LIGHT: Flashing

Steady

Steady

Steady

PROTECTION: Against overvoltages and stray currents in wiring, to reduce flickering phenomenon and withstand vibrations

Against overvoltages and to withstand vibrations

Selector switches

KNOB



2 position
LPC S1
20
21

3 position
LPC S1
30
31
32
33

LEVER



2 position
LPC S2
20
21

3 position
LPC S2
30
31
32
33

KNOB CAP



2 position
LPC S4
20
21

3 position
LPC S4
30
31
32
33

KEY



2 position
LPC S3
20
21
40

3 position
LPC S3
30
31
32
33
50

LPC S3
60
70
80
90

Version with Ronis keys

Types available with 5 different key codes; add "R" suffix to order code and complete with numeric code from the following: 421E, 458A, 520E, 3131A or 3433E.



Type of positions and rotation angles

- Maintained position
- Spring return position
- Key extraction position

2 position




3 position



Illuminated selector switches

2 POSITION KNOB



LPC SL12
03
04
05
06
08
13
14
15
16
18

3 POSITION KNOB



LPC SL13
03
04
05
06
08
13
14
15
16
18

LPC SL13
23
24
25
26
28
33
34
35
36
38

USB and RJ45 communication interfaces



LPC D

- USB 01 3.0 A-A connection type
- USB 03 3.0 A-B connection type
- USB 05 3.0 B-A connection type
- RJ45 06 Ethernet connection type (shielded)

Double-touch buttons, spring return

2 FLUSH



LPC B71
12
13
14
22
23
24
START/STOP 33

1 EXTENDED AND 1 FLUSH



LPC B72
12
13
14
22
23
24
START/STOP 33

Triple-touch buttons, spring return

2 EXTERNAL FLUSH AND 1 MIDDLE EXTENDED



LPC B73
STOP 45
STOP 65
STOP 55
STOP 75

Double-touch buttons, spring return, white indicator light

2 FLUSH



LPC BL71
12
13
14
22
23
24
START/STOP 33

1 EXTENDED AND 1 FLUSH



LPC BL72
12
13
14
22
23
24
START/STOP 33

Monoblock potentiometer drives



LPC PA
001 1 kΩ
002 2,5 kΩ
005 5 kΩ
010 10 kΩ
050 50 kΩ
100 100 kΩ
500 500 kΩ

Joysticks (IP65)



WITHOUT MECHANICAL INTERLOCK

8 LM2T J 200 400
201 401



WITH MECHANICAL INTERLOCK IN CENTRE POSITION

8 LM2T J 210 410
211 411

----- Instable positions

—— Stable positions

Pulse and steady tone monoblock buzzers



Supply voltage
9-15VAC/DC
18-30VAC/DC
85-140VAC/DC
185-265VAC/DC

IP40
LPC ZSA
LPC ZSB
LPC ZSE
LPC ZSM



Supply voltage
9-15VAC/DC
18-30VAC/DC
85-140VAC/DC
185-265VAC/DC

IP66
LPC ZSA IP
LPC ZSB IP
LPC ZSE IP
LPC ZSM IP

IP40: 90dB sound intensity at 10 cm.
IP66: 80dB sound intensity at 10 cm.

LED integrated monoblock pilot lights, steady light



LPM L
Voltage ↑ ↑ Colour
12VAC/DC A 3
24VAC/DC B 4
48VAC/DC D 5
120VAC E 6
230VAC M 7

PLatinum
Quality touch!

Order code	Description
 LPX A127	Transparent diffuser for double-touch buttons
LPX A130	Threaded plug for unused drilled holes (grey)
 LPX A140	Action plug for centre contact
LPX A150	Rod for mechanical reset button (l=150mm)
LPX A170	Spare standard key set for selector switches or mushroom head buttons, key code n° 455
LPX A170R ²	Spare key set for selector switches or mushroom head buttons, LPC.. R type
 LPX B0	Flush-extended spring return actuator with no cap or lens
LPX B3	Shrouded spring return actuator with no cap or lens

Order code	Description
LPXQ0	Flush-extended push-push actuator with no cap
LPXQL0	Illuminated flush-extended push-push actuator with no lens
 LPX B104	Flush cap for spring-return actuators.
LPX B102	Black
LPX B103	Green
LPX B104	Red
LPX B105	Yellow
LPX B106	Blue
LPX B108	White
 LPX B203	Extended cap for spring-return actuators.
LPX B202	Black
LPX B203	Green
LPX B204	Red
LPX B205	Yellow
LPX B206	Blue
LPX B208	White

Order code	Description
 LPX BL103	Flush lens for illuminated spring-return actuators.
LPX BL104	Green
LPX BL105	Red
LPX BL106	Yellow
LPX BL107	Blue
LPX BL108	Transparent
 LPX BL206	Extended lens for illuminated spring-return actuators.
LPX BL203	Green
LPX BL204	Red
LPX BL205	Yellow
LPX BL206	Blue
LPX BL207	Transparent

² Versions with different key code. Complete with the numeric code of the key. The following versions are available: 421E, 458A, 520E, 3131A, 3433E.



Order code	Description
LPX AU00	Threaded ring for actuator fixing
LPX AU100	Label holder for blank or engraved plastic LPX AU109 label
LPX AU109	Engravable silver plastic label to use with LPX AU100 holder
LPX AU105	Label holder for blank or engraved LPX AU108 label
LPX AU108	Engravable silver plastic label to use with LPX AU105 holder
LPX AU13 ³ ⁴	Rubber boot for flush button LPC B1/BL1/R1...
LPX AU14 ³ ⁴	Rubber boot for buttons LPC B2/B3/BL2/R2...
LPX AU157	Rubber boot for double and triple-touch buttons, transparent
LPX AU167 ⁴ ⁵	Rubber boot for mushroom head buttons, LPC B63/B66/B67/BL66..., transparent
LPX AU158 ⁴ ⁶	Padlockable protection, Ø5-8mm locks for buttons LPC B66/B67/B68/BL66...; for LPC B34... Ø5-6mm locks only
LPX AU159 ⁴ ⁶	Shroud for buttons LPC B63..., LPC B66/67/68/BL66...
LPX DIN ⁴ ⁶	Adapter for mounting LPC... buttons on DIN rail 35mm/1.38" wide (2 modules)
LPX P01	M20 cable gland with threaded ring for LPZ control stations
8 LM2T A161	Ø30mm hole size adapter set for 22mm (use 2 per hole)
8 LM2T A185	Selector protection shroud for knob type only
8 LM2T A200	Socket spanner/wrench for fixing ring fitting, metal

³ For flush and extended push buttons, complete the order code by adding the digit of the required colour: 2 (black); 3 (green); 4 (red); 5 (yellow); 6 (blue); 7 (transparent); 8 (white). For illuminated push buttons, add only digit 7 (transparent).
⁴ Cannot be used when LPX AU100 or LPX AU105 is fitted.
⁵ Cannot be used when LPX AU158 is fitted.
⁶ Cannot be used when LPX AU167 is fitted.

Plastic disk for mushroom head pushbuttons



Order code	Text
LPX AU113	EMERGENCY/STOP Ø90mm
LPX AU115	EMERGENCY/STOP Ø60mm
LPX AU118	ARRET D'URGENCE / NOT-AUS / PARO EMERGENCIA Ø60mm
LPX AU123	Emergency stop IEC 60417-5638 Ø60mm
LPX AU124	Emergency stop IEC 60417-5638 Ø90mm
LPX AU110	EMERGENCY STOP adhesive label, size 34.5x65mm

Labels with text for LPX AU100 legend holder

Order code	Text
General use.	
8 LM2T AU206	Blank for writing
8 LM2T AU207	Sheet with 108 labels for laser printing ⁷
8 LM2T AU208 ³	Sheet with 108 laser-printed labels ⁷
8 LM2T AGB216	CLOSE
8 LM2T AGB220	EMERGENCY
8 LM2T AGB231	FAST
8 LM2T AGB263	FAULT
8 LM2T AGB215	FORWARD
8 LM2T AGB228	LEFT
8 LM2T AGB218	LOWER
8 LM2T AGB221	OFF
8 LM2T AGB223	ON
8 LM2T AGB211	OPEN
8 LM2T AGB229	POWER ON
8 LM2T AGB227	RAISE

Order code	Text
8 LM2T AGB226	RESET
8 LM2T AGB222	REVERSE
8 LM2T AGB217	RIGHT
8 LM2T AGB241	RUNNING
8 LM2T AGB224	SLOW
8 LM2T AGB225	START
8 LM2T AGB230	STOP
8 LM2T AGB214	STOP RESET
8 LM2T AGB240	THERMAL FAULT
8 LM2T AGB237	TRIP
International labels for pushbuttons.	
8 LM2T AU200	0
8 LM2T AU201	I
8 LM2T AU202	II

Order code	Text
For selector switches.	
8 LM2T AI233	AUTO-MAN
8 LM2T AI234	AUTO-O-MAN
8 LM2T AI241	MAN-AUTO
8 LM2T AI242	MAN-O-AUTO
8 LM2T AGB235	FWD-O-REV
8 LM2T AGB236	OFF-ON
8 LM2T AGB232	STOP-START
International labels for selector switches.	
8 LM2T AU203	O-I
8 LM2T AU204	I-II
8 LM2T AU205	I-O-II

⁷ Recommended use with LPX AU109 blank label.
³ Complete code with required label text.



8 LM2T AGB230



● HIGH DEGREE OF PROTECTION

- IP66: Powerful water jets
- IP67: Water immersion at one metre
- IP69K: Powerful water jets at high pressure and temperature
- Type 4X: UL/CSA directives in regards powerful water jets.



● ELEGANT STYLE AND ERGONOMIC DESIGN

All the series elements have an ergonomic design and, at the same time, particular care has been given to detail aesthetics.



● LONG ACTUATOR MECHANICAL LIFE

- 5,000,000 cycles: Pushbutton actuators and mechanical reset buttons
- 1,000,000 cycles: Selectors, double and triple-touch actuators
- 300,000 cycles: Emergency-stop actuators.



● MATERIALS RESISTANT TO OILS, SOLVENTS AND HYDROCARBONS



● USAGE AT EXTREME TEMPERATURE CONDITIONS

Range between -25° and +70°C.



● INTERNATIONAL CERTIFICATIONS




● CONTACT ELEMENTS



- Miniaturised size
- High electric conductivity - 5V 1mA
- **Up to 9 contact elements** can be installed, 3 rows of 3 elements
- Available versions: Front and base mount with screw terminals while front-mount only with faston and spring-clamp terminals
- Contact operation with double breaking action, direct (positive) opening action and wiping effect.


● REDUCED DIMENSIONS AND INTERAXIS



- Minimum pitch between drillings:
- 30x40mm for two single actuators on a mounting surface
 - 30x55mm for double and triple-touch actuators or when spring clamp contacts are used.



- Total depth, from the external mounting surface to the end of the first contact element is just **43mm**.



- **Low actuator profile**
The external actuator bezel has a low profile and reduced front thickness.



ENERGY AND AUTOMATION

www.LovatoElectric.com

LOVATO ELECTRIC S.P. A.

via Don E. Mazza, 12
24020 Gorle (Bergamo) Italy

Tel +39 035 4282111
Fax +39 035 4282200
info@LovatoElectric.com



Follow us

The products described in this publication are subject to be revised or improved at any moment. Catalogue descriptions and details, such as technical and operational data, drawings, diagrams and instructions, etc., do not have any contractual value. In addition, products should be installed and used by qualified personnel and in compliance with the regulations in force for electrical systems in order to avoid damages and safety hazards.