



1000W Modified Sine Wave DC-AC Power Inverter **A301/302-1K0 series**



■ Features :

- 12V or 24V DC input
- Power ON-OFF switch
- Input voltage range: -15% ~ +25%
- Output voltage regulation: ±10%
- Protections: Bat. Low alarm/Bat. Low shutdown/Over voltage/Over temp./Output short/Input polarity reverse/Over load.
- Output waveform: Modified sine wave
- Cooling fan ON-OFF control
- ON/OFF remote control(Optional)
- Approvals: E13/ EAC / CE / UKCA
- 1 year warranty



SPECIFICATION

SPECIFICATION						
ORDER NO.		A301-1K0-B2		A301-1K0-F3	A302-1K0-B2	A302-1K0-F3
OUTPUT	SAFETY MODEL NO.	A301-1K0			A302-1K0	
	AC VOLTAGE	110V	230V		110V	230V
	RATED POWER	1000W				
	PEAK POWER	1200W<30min.				
	SURGE POWER	2400W				
	WAVEFORM	Modified Sine Wave				
	FREQUENCY	60Hz±1%	50Hz±1%		60Hz±1%	50Hz±1%
	AC REGULATION	±10%			±10%	
	STANDARD RECEPTACLES	TYPE-2* 3ea	TYPE-3* 2ea		TYPE-2* 3ea	TYPE-3* 2ea
LED INDICATOR	Green LED for power on; Yellow LED for O.T.P.; Red LED for power failure status					
INPUT	DC CURRENT	110A			55A	
	NO LOAD CURRENT DRAW	0.4A			0.2A	
	DC VOLTAGE	12V			24V	
	VOLTAGE RANGE	10 ~ 15VDC			21 ~ 30VDC	
	EFFICIENCY (Typ.)	82%			85%	
	DC CONNECTOR	1000mm R type terminal			1000mm R type terminal	
	FUSE	30A*5			20A*5	
PROTECTION	BAT. LOW ALARM	10±0.5V			21±0.8V	
	BAT. LOW SHUTDOWN	9.5±0.5V			20±0.8V	
	OVER LOAD	>1200W shut down o/p voltage, re-power to recover				
	OVER VOLTAGE	15 ~ 16V			29 ~ 31V	
	OVER TEMPERATURE	60±5℃ / 140±9°F				
	OUTPUT SHORT	Shut-off				
	BAT. POLARITY	By fuse open				
ENVIRONMENT	WORKING TEMP.	0 ~ 30℃ @ 100% load, 40℃ @ 70% load				
	WORKING HUMIDITY	20% ~ 90% RH non-condensing				
	STORAGE TEMP., HUMIDITY	-30 ~ +70℃ / -22 ~ +158°F, 10 ~ 95% RH				
	TEMP. COEFFICIENT	±0.05% / °C (0 ~ 50℃)				
SAFETY & EMC	SAFETY STANDARDS	EAC TP TC 004 approved				
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25℃ / 70% RH				
	EMI RADIATION	Compliance to BS EN/EN55014-1, EAC TP TC 020				
	EMS IMMUNITY	Compliance to BS EN/EN55014-2, IEC61000-4-2,3, EAC TP TC 020				
	LVD	Compliance to BS EN/EN62368-1				
OTHERS	MTBF	98Khrs min. MIL-HDBK-217F (25℃)				
	DIMENSION	310*210*85mm (L*W*H)				
	PACKING	3.3kg ; 4pcs / 17.5kg / CARTON				
	COOLING	>40℃ (NTC) fan on				
	APPLICATIONS	Home appliance, Power tools, Office and Portable equipment and Vehicle ...etc.				

■ AC Output Receptacles (optional)

TYPE-1	TYPE-2	TYPE-3	TYPE-4	TYPE-5	TYPE-6
JAPAN	USA	EUROPE	UNIVERSAL	AUSTRALIA	U.K

Mechanical Specification

Unit:mm

