



240W DIN Rail Type DC-DC Converter

DDR-240 series




■ Features

- Compliance to BS EN/EN50155 and BS EN/EN45545-2 railway standard
- Width only 40mm
- 2:1 wide input range
- -40~+70°C wide working temperature
- 150% peak load capability
- Current sharing up to 960W(3+1)
- DC output adjustable
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- Protections: Short circuit / Overload / Over voltage / Over temperature / Input reverse polarity / Input under voltage protection
- 4KVdc I/O isolation(Reinforced isolation)
- DC OK relay contact
- Remote ON-OFF control
- 3 years warranty

■ Description

DDR-240 series is a 240W DIN Rail type DC-DC converter with main features including DIN rail-type easy installation, ultra slim width (40mm), 2:1 wide input voltage, fanless design, -40~+70°C wide operating temperature, 4KVdc I/O isolation, 150% peak load, current sharing, DC OK, adjustable output voltage and full protective functions. This series of models has various input options: 16.8~33.6V / 33.6~67.2V / 67.2~154V and two output options: 24V / 48V and can be used for industrial & railway control, security control, communication system and other fields. Suitable applications include to DC buck/boost regulator, increasing system insulation level and voltage drop compensation along cable...etc.

■ Model Encoding



■ Applications

- Bus, tram, metro or railway system
- Industrial control system
- Semi-conductor fabrication equipment
- Factory automation
- Electro-mechanical
- Wireless network
- Telecom or datacom system

SPECIFICATION


MODEL		DDR-240B-24	DDR-240B-48	DDR-240C-24	DDR-240C-48	DDR-240D-24	DDR-240D-48																			
OUTPUT	DC VOLTAGE	24V	48V	24V	48V	24V	48V																			
	RATED CURRENT	10A	5A	10A	5A	10A	5A																			
	CURRENT RANGE	0 ~ 10A	0 ~ 5A	0 ~ 10A	0 ~ 5A	0 ~ 10A	0 ~ 5A																			
	RATED POWER	240W	240W	240W	240W	240W	240W																			
	PEAK CURRENT	15A	7.5A	15A	7.5A	15A	7.5A																			
	POWER Note.5	360W (3sec.)																								
	RIPPLE & NOISE (max.) Note.2	80mVp-p	100mVp-p	80mVp-p	100mVp-p	80mVp-p	100mVp-p																			
	VOLTAGE ADJ. RANGE	24 ~ 28V	48 ~ 56V	24 ~ 28V	48 ~ 56V	24 ~ 28V	48 ~ 56V																			
	VOLTAGE TOLERANCE Note.3	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%																			
	LINE REGULATION	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%																			
INPUT	LOAD REGULATION	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%																			
	SETUP, RISE TIME	500ms, 60ms																								
	HOLD UP TIME (Typ.)	Please refer to page 6 Hold up Time(Load de-rating curve)																								
	VOLTAGE RANGE Note.4	100ms	CONTINUOUS	16.8 ~ 33.6Vdc	33.6 ~ 67.2Vdc	67.2 ~ 154Vdc																				
				14.4 ~ 16.8Vdc	28.8 ~ 33.6Vdc	66 ~ 67.2Vdc																				
PROTECTION	EFFICIENCY (Typ.)	90%	90%	91%	92%	92%	92.5%																			
	DC CURRENT (Typ.)	11.2A @24Vdc		5.6A @48Vdc		2.5A @110Vdc																				
	INRUSH CURRENT (Typ.)	30A																								
	INTERRUPTION OF VOLTAGE SUPPLY	EN50155:2007-B/C- type comply with S2 level (10ms)@ 70% load ; D-type comply with S2 level (10ms)@ full load																								
		EN50155:2017-Comply with S1 level																								
FUNCTION	OVERLOAD Note.5	Normally works within 150% rated output power for more than 3 seconds and then constant current protection 105~135% rated output power with auto-recovery																								
	OVER VOLTAGE	28.8 ~ 35V	57.6 ~ 65.0V	28.8 ~ 35V	57.6 ~ 65V	28.8 ~ 35V	57.6 ~ 65V																			
	OVER TEMPERATURE	Protection type : Shut down o/p voltage, re-power on to recover																								
	UNDER VOLTAGE LOCKOUT	24Vin (B - type):Power ON \geqslant 16.8V , OFF \leqslant 16.5V		48Vin (C - type):Power ON \geqslant 33.6V , OFF \leqslant 33V		110Vin (D - type):Power ON \geqslant 67.2V , OFF \leqslant 65V																				
	DC OK REALY CONTACT RATINGS (max.)	30Vdc/1A resistive load																								
ENVIRONMENT	CURRENT SHARING	Up to 960W (3+1 units). Please refer to the Function Manual																								
	REMOTE ON-OFF CONTROL	Please refer to the Function Manual																								
	WORKING TEMP.	-40 ~ +70°C (Refer to "Derating Curve")																								
	WORKING HUMIDITY	5 ~ 95% RH non-condensing																								
	STORAGE TEMP., HUMIDITY	-40 ~ +85, 5 ~ 95% RH non-condensing																								
SAFETY & EMC (Note 6)	TEMP. COEFFICIENT	$\pm 0.03\%/\text{°C}$ (0 ~ 55°C)																								
	VIBRATION	Component:10 ~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes; Mounting: Compliance to IEC61373																								
	OPERATING ALTITUDE Note.7	5000 meters																								
	SAFETY STANDARDS	IEC 62368-1, UL 62368-1, EAC TP TC 004, AS/NZS 62368.1 approved																								
	WITHSTAND VOLTAGE	I/P-O/P:4KVdc I/P-FG:2.5KVdc O/P-FG:0.71KVdc																								
OTHERS	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG: >100 M Ohms / 500Vdc / 25°C / 70% RH																								
	EMC EMISSION	Parameter	Standard	Test Level / Note																						
		Conducted	BS EN/EN55032	Class B																						
		Radiated	BS EN/EN55032	Class B																						
		Voltage Flicker	BS EN/EN61000-3-3	----																						
	EMC IMMUNITY	Harmonic Current	----	----																						
		BS EN/EN55024 , BS EN/EN61000-6-2(BS EN/EN50082-2)																								
		Parameter	Standard	Test Level / Note																						
		ESD	BS EN/EN61000-4-2	Level 3, 8KV air ; Level 3, 6KV contact; criteria A																						
		Radiated	BS EN/EN61000-4-3	Level 3, 10V/m ; criteria A																						
	RAILWAY STANDARD	EFT / Burst	BS EN/EN61000-4-4	Level 3, 2KV ; criteria A																						
		Surge	BS EN/EN61000-4-5	Level 3, 1KV/Line-Line ;Level 3, 2KV/Line-Line-FG ;criteria A																						
		Conducted	BS EN/EN61000-4-6	Level 3, 10V ; criteria A																						
		Magnetic Field	BS EN/EN61000-4-8	Level 4, 30A/m ; criteria A																						
NOTE	Compliance to BS EN/EN45545-2 for fire protection ; Meet BS EN/EN50155 / IEC60571 including IEC61373 for shock & vibration, BS EN/EN50121-3-2 for EMC																									
	MTBF	484.9K hrs min. Telcordia SR-332 (Bellcore) ; 189.9K hrs min. MIL-HDBK-217F (25°C)																								
	DIMENSION	40*125.2*113.5mm (W*H*D)																								
NOTE	PACKING	0.76Kg;20psc/16.2Kg/1.16CUFT																								
	1. All parameters NOT specially mentioned are measured at normal input (B:24Vdc , C:48Vdc , D:110Vdc) , rated load and 25°C of ambient temperature.																									
	2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 μ f & 47 μ f parallel capacitor.																									
3. Tolerance : includes set up tolerance, line regulation and load regulation.																										
4. Derating may be needed under low input voltage. Please check the derating curve for more details.																										
5. 3 seconds max., please refer to peak loading curves.																										
6. The power supply is considered as an independent unit, but the final equipment still need to re-confirmed that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on http://www.meanwell.com)																										
7. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft).																										
※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx																										




240W DIN Rail Type DC-DC Converter

DDR-240 series


■ Block Diagram





■ Derating Curve



■ Output derating VS input voltage



■ Peak Loading




■ DC OK Relay Contact

Contact Close	PSU turns on / DC OK.
Contact Open	PSU turns off / DC Fail.
Contact Ratings (max.)	30V/1A resistive load.

■ Function Manual

1. Current sharing

- (1) Parallel operation is available by connecting the units shown as below (P+,P- are connected mutually in parallel) :
- (2) The voltage difference among each output should be minimized that less than 0.2V is required.
- (3) The total output current must not exceed the value determined by the following equation (Output current at parallel operation)
=(The rated current per unit) x (Number of unit) x 0.9.
- (4) In parallel operation 4 units is the maximum, please consult the manufacturer for other applications.
- (5) When in parallel operation, the minimum output load should be greater than 3% of total output load.
(Min. load > 3% rated current per unit x number of unit)



2. Remote ON-OFF Control

※ The power supply can be turned ON-OFF by using the "Remote ON-OFF" function.

Remote ON-OFF (TB1 PIN2,4)	Output Status
Open or 4 ~ 10VDC	power supply ON
Short or 0 ~ 0.8VDC	power supply OFF



240W DIN Rail Type DC-DC Converter

DDR-240 series

■ Input Fuse


There is one fuse connected in series to the positive input line, which is used to protect against abnormal surge. Fuse specifications of each model are shown as below.

Type	Fuse Type	Reference and Rating
B	Time-Lag	Conquer MST, 10A, 250V *2
C	Time-Lag	Conquer MST, 6.3A, 250V *2
D	Time-Lag	Conquer MST, 6.3A, 250V *1


■ Input Under-Voltage Protection

If input voltage drops below V_{min} , the internal control IC shuts down and there is no output voltage. It recovers automatically when input voltage reaches above V_{min} , please refer to the curve below.


DDR-240B-24



DDR-240C-24



DDR-240D-24



■ Input Reverse Polarity Protection

There is a MOSFET connected in series to the negative input line. If the input polarity is connected reversely, the MOSFET opens and there will be no output to protect the unit.

■ Inrush Current


Inrush current is suppressed by a resistor during the initial start-up, and then the resistor is bypassed by a MOSFET to reduce power consumption after accomplishing the start-up.

■ Hold-up Time

- EN50155: 2007 version - B/C-type comply with S2 level (10ms)@ 70% load ; D-type comply with S2 level (10ms)@ full load,
Please refer to the table and curves show below for the hold up time specification.


Model \ Load	100% load	70% load	other load
B type (24Vin)	6ms min.	10ms min.	figure 1,2
C type (48Vin)	8ms min.	11ms min.	figure 3,4
D type (110Vin)	11ms min.	15ms min.	figure 5,6

DDR-240B-24




(figure 1)

DDR-240B-48




(figure 2)

DDR-240C-24




(figure 3)

DDR-240C-48




(figure 4)

DDR-240D-24



(figure 5)

DDR-240D-48



(figure 6)

- EN50155: 2017 version - Comply with S1 level




240W DIN Rail Type DC-DC Converter

DDR-240 series


■ Efficiency vs Load & Vin Curve

The efficiency vs load & Vin curves of each model are shown as below.


DDR-240B-24




DDR-240B-48




DDR-240C-24




DDR-240C-48



DDR-240D-24



DDR-240D-48



■ Immunity to Environmental Conditions

Test method	Standard	Test conditions	Status
Cooling Test	EN 50155 section 12.2.3 (Column 2, Class TX) EN 60068-2-1	Temperature: -40°C Dwell Time: 2 hrs/cycle	No damage
Dry Heat Test	EN 50155 section 12.2.4 (Column 2, Class TX) EN 50155 section 12.2.4 (Column 3, Class TX & Column 4, Class TX) EN 60068-2-2	Temperature: 70°C / 85°C Duration: 6 hrs / 10min	PASS
Damp Heat Test, Cyclic	EN 50155 section 12.2.5 EN 60068-2-30	Temperature: 25°C~55°C Humidity: 90%~100% RH Duration: 48 hrs	PASS
Vibration Test	EN 50155 section 12.2.11 EN 61373	Temperature: 19°C Humidity: 65% Duration: 10 mins	PASS
Increased Vibration Test	EN 50155 section 12.2.11 EN 61373	Temperature: 19°C Humidity: 65% Duration: 5 hrs	PASS
Shock Test	EN 50155 section 12.2.11 EN 61373	Temperature: 21± 3°C Humidity: 65 ± 5% Duration: 30ms*18	PASS
Low Temperature Storage Test	EN 50155 section 12.2.3 (Column 2, Class TX) EN 60068-2-1	Temperature: -40°C Dwell Time: 16 hrs	PASS
Salt Mist Test	EN 50155 section 12.2.10 (Class ST4)	Temperature: 35°C ±2°C Duration: 96 hrs	PASS

■ EN45545-2 Fire Test Conditions

Test Items			Hazard Level		
	Items	Standard	HL1	HL2	HL3
R22	Oxygen index test	EN 45545-2:2013 EN ISO 4589-2:1996	PASS	PASS	PASS
	Smoke density test	EN 45545-2:2013 EN ISO 5659-2:2006	PASS	PASS	PASS
	Smoke toxicity test	EN 45545-2:2013 NF X70-100:2006	PASS	PASS	PASS
R24	Oxygen index test	EN 45545-2:2013 EN ISO 4589-2:1996	PASS	PASS	PASS
R25	Glow-wire test	EN 45545-2:2013 EN 60695-2-11:2000	PASS	PASS	PASS
R26	Vertical flame test	EN 45545-2:2013 EN 60695-11:2003	PASS	PASS	PASS




240W DIN Rail Type DC-DC Converter


DDR-240 series

■ Mechanical Specification


Case No.265A-D Unit:mm




Top View




Side View



Front View



Side View



Bottom View


Terminal Pin No. Assignment (TB2,TB3)

Pin No.	Assignment
1,2	DC output +Vo
5,6	DC output -Vo
3,4	DC OK Relay Contact
7,8	P+,P-

Terminal Pin No. Assignment (TB1)

Pin No.	Assignment
1	FG
2	DC input -Vin
3	DC input +Vin
4	Remote ON/OFF

■ Installation Instruction



ADMISSIBLE DIN-RAIL:TS35/7.5 OR TS35/15
(For reference only. Not included with unit.)

This series fits DIN rail TS35/7.5 or TS35/15.
For installation details, please refer to the Instruction manual.

■ Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>