



■ Features :

- Universal AC input / Full range
- Built-in active PFC function
- High efficiency up to 93%
- Withstand 300VAC surge input for 5 seconds
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Built-in 12V/0.5A auxiliary output
- 5"x3" compact size
- Free air convection for 200W and 300W with 20.5 CFM forced air
- With power good and fail signal output
- Built-in remote sense function
- No load power consumption under 0.5W by PS-ON control
- Standby 5V@1A with fan, @ 0.6A without fan
- Operating altitude up to 5000 meters
- 3 years warranty


User's Manual



SPECIFICATION

MODEL	EPP-300-12	EPP-300-15	EPP-300-24	EPP-300-27	EPP-300-48
OUTPUT	DC VOLTAGE	12V	15V	24V	27V
	RATED CURRENT (20.5CFM)	25A	20A	12.5A	11.12A
	CURRENT RANGE (convection)	0 ~ 16.67A	0 ~ 13.33A	0 ~ 8.33A	0 ~ 7.4A
	CURRENT RANGE (20.5CFM)	0 ~ 25A	0 ~ 20A	0 ~ 12.5A	0 ~ 11.12A
	RATED POWER (convection)	200W	200W	199.9W	199.8W
	RATED POWER (20.5CFM)	300W	300W	300W	300W
	RIPLPE & NOISE (max.) Note.2	120mVp-p	120mVp-p	150mVp-p	200mVp-p
	VOLTAGE ADJ. RANGE	Main output:11.4 ~ 12.6V	Main output:14.25 ~ 15.75V	Main output:22.8 ~ 25.2V	Main output:25.65 ~ 28.35V
	VOLTAGE TOLERANCE Note.3	± 3.0%	± 3.0%	± 2.0%	± 2.0%
	LINE REGULATION	± 0.5%	± 0.5%	± 0.5%	± 0.5%
INPUT	LOAD REGULATION	± 1.0%	± 1.0%	± 1.0%	± 1.0%
	SETUP, RISE TIME	2500ms, 30ms/230VAC	3000ms, 30ms/115VAC at full load		
	HOLD UP TIME (Typ.)	13ms/230VAC/115VAC at full load			
	VOLTAGE RANGE Note.5	90 ~ 264VAC	127 ~ 370VDC		
	FREQUENCY RANGE	47 ~ 63Hz			
PROTECTION	POWER FACTOR (Typ.)	PF>0.93/230VAC	PF>0.98/115VAC at full load		
	EFFICIENCY (Typ.)	90%	90%	92.5%	93%
	AC CURRENT (Typ.)	3.5A/115VAC	1.8A/230VAC		
	INRUSH CURRENT (Typ.)	COLD START 40A/115VAC	80A/230VAC		
	LEAKAGE CURRENT	<2mA/240VAC			
PROTECTION	OVERLOAD	105 ~ 135% rated output power			
		Protection type : Hiccup mode, recovers automatically after fault condition is removed			
	OVER VOLTAGE	13.5 ~ 15V	16.2 ~ 18.5V	26 ~ 30V	29.5 ~ 33.5V
		Protection type : Shut down o/p voltage, re-power on to recover			
	OVER TEMPERATURE	110°C ± 5°C (TSW1) detect on heatsink of power transistor			
FUNCTION		115 ± 5°C (12V,15V),85 ± 5°C (24V,27V,48V) (TSW2) detect on heatsink of output diode			
		Protection type : (TSW1) Shut down o/p voltage, recovers automatically after temperature goes down			
		Protection type : (TSW2) Shut down o/p voltage, re-power on to recover			
	5V STANDBY	5VSB : 5V@0.6A without fan, 1A with fan 20.5CFM ; tolerance ± 2%, ripple : 150mVp-p(max.)			
	AUXILIARY POWER (AUX)	12V@0.5A for driving a fan ; tolerance -15% ~ +10%			
ENVIRONMENT	PS-ON INPUT SIGNAL	Power on: PS-ON = "Hi" or > 2 ~ 5V ; Power off: PS-ON = "Low" or < 0 ~ 0.5V"			
	POWER GOOD / POWER FAIL	500ms>PG>10ms ; The TTL signal goes high with 10ms to 500ms delay after power set up ; The TTL signal goes low at least 1ms before Vo below 90% of rated value			
	WORKING TEMP.	-30 ~ +70°C (Refer to "Derating Curve")			
	WORKING HUMIDITY	20 ~ 90% RH non-condensing			
	STORAGE TEMP., HUMIDITY	-40 ~ +85°C , 10 ~ 95% RH			
SAFETY & EMC (Note 4)	TEMP. COEFFICIENT	± 0.03%/°C (0 ~ 50°C)			
	OPERATING ALTITUDE Note.7	5000 meters			
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes			
	SAFETY STANDARDS	UL62368-1, TUV BS EN/EN62368-1, EAC TP TC 004 approved			
	WITHSTAND VOLTAGE	I/P-O/P:3kVAC I/P-FG:2kVAC O/P-FG:0.5kVAC			
OTHERS	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70% RH			
	EMC EMISSION	Compliance to BS EN/EN55032 (CISPR32),Conduction Class B,Radiation Class B;BS EN/EN61000-3-2,3;EAC TP TC 020			
	EMC IMMUNITY	Compliance to BS EN/EN61000-4-2,3,4,5,6,8,11, BS EN/EN55024, BS EN/EN60601-1-2, criteria A, EAC TP TC 020			
	MTBF	160Khrs min. MIL-HDBK-217F (25°C)			
	DIMENSION	127*76.2*35mm (L*W*H)			
NOTE	PACKING	0.37 Kg; 36pcs/14.3Kg/0.96CUFT;			
	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (available on http://www.meanwell.com) 5. Derating may be needed under low input voltages. Please check the derating curve for more details. 6. Heat Sink HS1,HS2 can not be shorted. 7. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft). ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx				

■ Mechanical Specification



Unit:mm

AC Input Connector (CN1) : JST B5P-VH or equivalent

Pin No.	Assignment	Mating Housing	Terminal
1	AC/N		
2,4	No Pin		
3	AC/L	JST VHR or equivalent	JST SVH-21T-P1.1 or equivalent
5	FG \pm		

DC Output Connector (CN2,CN3)

Pin No.	Assignment	Output Terminals
CN2	-V	M3.5 Pan HD screw in 2 positions
CN3	+V	Torque to 8 lbs-in(90cNm)max.

Function Connector(CN100):HRS DF11-4DP-2DS or equivalent

Pin No.	Status	Mating Housing	Terminal
1	-S		
2	+S		
3	DC COM	HRS DF11-4DS or equivalent	HRS DF11-**SC or equivalent
4	PG		

Function Connector(CN951):HRS DF11-4DP-2DS or equivalent


Pin No.	Status	Mating Housing	Terminal
1	5VSB		
2,4	DC COM	HRS DF11-4DS or equivalent	HRS DF11-**SC or equivalent
3	PS-ON		

FAN Connector(CN952) : JST S2B-XH or equivalent


Pin No.	Assignment	Mating Housing	Terminal
1	DC COM		JST XHP or equivalent
2	+12V		JST SXH-001T-P0.6 or equivalent

 PFC fosc : 65KHz
 PWM fosc : 70KHz

■ Block Diagram



■ Derating Curve



■ Output Derating VS Input Voltage

