



## ■ Features


- Ultra slim design with 105mm(6SU) width
- Universal input 85~264VAC(277VAC operational)
- No load power consumption<0.3W
- Isolation class II
- DC output voltage adjustable
- Protections : Short circuit / Overload / Over voltage
- Cooling by free air convection
- DIN rail TS-35/7.5 or 15 mountable
- Over voltage category III
- LED indicator for power on
- 3 years warranty

## ■ Description

HDR-150 is an economical ultra slim 150W DIN rail power supply series, adapt to be installed on TS-35/7.5 or TS-35/15 mounting rails. The body is designed 105mm(6SU) in width, which allows space saving inside the cabinets. The entire series adopts the full range AC input from 85VAC to 264VAC(277VAC operational) and conforms to BS EN/EN61000-3-2, the norm the European Union regulates for harmonic current.

HDR-150 is designed with plastic housing that it can effectively prevent user from electric hazards. With working efficiency up to 90.5%, the entire series can operate at the ambient temperature between -30°C and 70°C under air convection. The complete protection functions and relevant certificates for home automations and industrial control apparatus (IEC62368-1,UL62368-1,UL61010, BS EN/EN61558-2-16) make HDR-150 a very competitive power supply solution for household and industrial applications.

## ■ Model Encoding



## ■ Applications

- Household control system
- Building automation
- Industrial control system
- Factory automation
- Electro-mechanical apparatus

**SPECIFICATION**


MODEL		HDR-150-12	HDR-150-15	HDR-150-24	HDR-150-48						
OUTPUT	DC VOLTAGE	12V	15V	24V	48V						
	RATED CURRENT	115VAC 10.2A	8.55A	5.31A	2.72A						
		230VAC 11.3A	9.5A	6.25A	3.2A						
	RATED POWER	115VAC 122.4W	128.3W	127.4W	130.6W						
		230VAC 135.6W	142.5W	150W	153.6W						
	RIPLPE & NOISE (max.) Note.2	100mVp-p	120mVp-p	150mVp-p	200mVp-p						
	VOLTAGE ADJ. RANGE	10.8~13.8V	13.5~18V	21.6~29V	43.2~55.2V						
	VOLTAGE TOLERANCE Note.3	±2.0%	±1.0%	±1.0%	±1.0%						
	LINE REGULATION	±1.0%	±1.0%	±1.0%	±1.0%						
	LOAD REGULATION	±1.0%	±1.0%	±1.0%	±1.0%						
INPUT	SETUP, RISE TIME	500ms, 60ms/230VAC	500ms, 60ms/115VAC at full load								
	HOLD UP TIME (Typ.)	30ms/230VAC	12ms/115VAC at full load								
PROTECTION	VOLTAGE RANGE	85~264VAC (277VAC operational)	120~370VDC (390VDC operational)								
	FREQUENCY RANGE	47~63Hz									
	EFFICIENCY (Typ.)	89%	89.5%	90.5%	90.5%						
	AC CURRENT (Typ.)	3A/115VAC	1.6A/230VAC								
	INRUSH CURRENT (Typ.)	COLD START 35A/115VAC	70A/230VAC								
ENVIRONMENT	OVERLOAD	105~135% rated output power									
		Hiccup mode when output voltage <50%, recovers automatically after fault condition is removed									
		Constant current limiting within 50%~100% rated output voltage, recovers automatically after fault condition is removed									
	OVER VOLTAGE	14.2~16.2V	18.8~22.5V	30~36V	56.5~64.8V						
		Protection type : Shut down o/p voltage, re-power on to recover									
	WORKING TEMP.	-30~+70°C (Refer to "Derating Curve")									
	WORKING HUMIDITY	20~90% RH non-condensing									
	STORAGE TEMP., HUMIDITY	-40~+85°C, 10~95% RH non-condensing									
	TEMP. COEFFICIENT	±0.03%/°C (0~45°C) RH non-condensing									
	VIBRATION	10~500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes; Mounting: Compliance to IEC60068-2-6									
	OPERATING ALTITUDE	2000 meters (Note 4)									
	OVER VOLTAGE CATEGORY	III ; According to EN62368,EN61558, EN50178,EN60664-1, EN62477-1 ; altitude up to 2000 meters									
SAFETY & EMC (Note.7)	SAFETY STANDARDS	IEC62368-1, UL62368-1, UL61010, TUV BS EN/EN61558-2-16, BS EN/EN61558-1, EAC TP TC 004 approved; Design refer to BS EN/EN50178, TUV BS EN/EN62368-1									
	WITHSTAND VOLTAGE	I/P-O/P:4kVAC									
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH									
	EMC EMISSION	Parameter	Standard	Test Level / Note							
		Conducted	BS EN/EN55032(CISPR32)	Class B							
		Radiated	BS EN/EN55032(CISPR32)	Class B (note 5)							
		Harmonic Current (Note 6)	BS EN/EN61000-3-2	Class A							
		Voltage Flicker	BS EN/EN61000-3-3	-----							
	EMC IMMUNITY	BS EN/EN55024, BS EN/EN61000-6-2									
		Parameter	Standard	Test Level / Note							
		ESD	BS EN/EN61000-4-2	Level 3, 8KV air; Level 2, 4KV contact, criteria A							
		Radiated Susceptibility	BS EN/EN61000-4-3	Level 3, criteria A							
		EFT/Burst	BS EN/EN61000-4-4	Level 3, criteria A							
		Surge	BS EN/EN61000-4-5	Level 4, 2KV/L-N, criteria A							
		Conducted	BS EN/EN61000-4-6	Level 3, criteria A							
		Magnetic Field	BS EN/EN61000-4-8	Level 4, criteria A							
		Voltage Dips and interruptions	BS EN/EN61000-4-11	>95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods							
OTHERS	MTBF	536K hrs min. MIL-HDBK-217F (25°C)									
	DIMENSION	105*90*54.5mm (W*H*D)									
	PACKING	0.31Kg; 32pcs/11Kg/1.0CUFT									
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF & 47μF parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft). 5. When the input voltage is 230VAC, delivers EMI Class B for radiated emission for the power supply; When the input voltage is 110VAC, delivers EMI Class A for radiated emission for the power supply. 6. Harmonic current test at 70% load. 7. The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on <a href="http://www.meanwell.com">http://www.meanwell.com</a> )										
	※ Product Liability Disclaimer : For detailed information, please refer to <a href="https://www.meanwell.com/serviceDisclaimer.aspx">https://www.meanwell.com/serviceDisclaimer.aspx</a>										




150W Ultra Slim Step Shape DIN Rail

**HDR-150** series


■ Block Diagram






■ Derating Curve VS Ambient Temperature



■ Output Derating VS Input Voltage



**■ Mechanical Specification**

 (Unit: mm , tolerance  $\pm 0.5\text{mm}$ )


ADMISSIBLE DIN-RAIL:TS35/7.5 OR TS35/15

**Terminal Pin No. Assignment**

Pin No.	Assignment	Pin No.	Assignment
1	AC/N	3,4	-V
2	AC/L	5,6	+V

**■ Installation Manual**

 Please refer to : <http://www.meanwell.com/manual.html>