




## ■ Features :

- Universal AC input / Full range
- Protections: Short circuit / Over current / Over voltage
- Built-in active PFC function
- Cooling by free air convection
- Class 2 power unit
- Output current level adjustable
- 100% full load burn-in test
- High reliability
- Suitable for built-in applications of LED lighting
- 2 years warranty




BS EN/EN61347-1-2-13

**SPECIFICATION**

MODEL	PLP-30-12	PLP-30-24	PLP-30-48
OUTPUT	<b>DC VOLTAGE</b>	12V	24V
	CONSTANT CURRENT REGION Note.5	9 ~ 12V	18 ~ 24V
	<b>RATED CURRENT</b>	2.5A	1.3A
	<b>CURRENT RANGE</b>	0 ~ 2.5A	0 ~ 1.3A
	<b>RATED POWER</b>	30W	31.2W
	<b>RIPPLE &amp; NOISE (max.) Note.2</b>	2Vp-p	2.4Vp-p
	<b>CURRENT ADJ. RANGE</b>	1.875 ~ 2.5A	0.975 ~ 1.3A
	<b>VOLTAGE TOLERANCE Note.3</b>	±10%	
	<b>LINE REGULATION</b>	±3.0%	
	<b>LOAD REGULATION</b>	±5.0%	
INPUT	<b>SETUP TIME</b>	500ms / 230VAC 1200ms / 115VAC at full load	
	<b>VOLTAGE RANGE Note.4</b>	90 ~ 264VAC 127 ~ 370VDC	
	<b>FREQUENCY RANGE</b>	47 ~ 63Hz	
	<b>POWER FACTOR (Typ.)</b>	PF>0.9 at 75 ~ 100% load , 115VAC / 230VAC	
	<b>TOTAL HARMONIC DISTORTION</b>	THD< 20% when output loading≥75% at 115VAC/230VAC input	
	<b>EFFICIENCY (Typ.)</b>	83% 85.5%	86.5%
	<b>AC CURRENT (Typ.)</b>	0.4A/115VAC 0.2A/230VAC	
	<b>INRUSH CURRENT (max.)</b>	COLD START 25A(twidth=45μs measured at 50% Ipeak) at 230VAC	
	<b>MAX.No. of PSUs on 16A CIRCUIT BREAKER</b>	64units (circuit breaker of type B) / 64 units (circuit breaker of type C) at 230VAC	
	<b>LEAKAGE CURRENT</b>	<0.75mA / 240VAC	
PROTECTION	<b>OVER CURRENT Note.5</b>	100 ~ 110%	
		Protection type : Constant current limiting, recovers automatically after fault condition is removed	
	<b>SHORT CIRCUIT</b>	Hiccup mode, recovers automatically after fault condition is removed.	
		15 ~ 18V 28 ~ 33V 57 ~ 63V	
ENVIRONMENT	<b>OVER VOLTAGE</b>	Protection type : Shut down o/p voltage, re-power on to recover	
	<b>WORKING TEMP.</b>	-30 ~ +70°C (Refer to "Derating Curve")	
	<b>WORKING HUMIDITY</b>	20 ~ 95% RH non-condensing	
	<b>STORAGE TEMP., HUMIDITY</b>	-40 ~ +80°C, 10 ~ 95% RH	
	<b>TEMP. COEFFICIENT</b>	±0.03%/°C (0 ~ 50°C)	
SAFETY & EMC	<b>VIBRATION</b>	10 ~ 500Hz, 2G 12min./1cycle, period for 72min. each along X, Y, Z axes	
	<b>SAFETY STANDARDS</b>	GB19510.1,GB19510.14,UL8750, TUV BS EN/EN61347-1, BS EN/EN61347-2-13, CSA C22.2 No. 250.0-08(except for 48V), EAC TP TC 004 approved ; design refer to UL60950-1	
	<b>WITHSTAND VOLTAGE</b>	I/P-O/P:3.75KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC	
	<b>ISOLATION RESISTANCE</b>	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70% RH	
	<b>EMC EMISSION</b>	Compliance to GB17625,GB17743,BS EN/EN55015, BS EN/EN61000-3-2 Class C (≥75% load); BS EN/EN61000-3-3,EAC TP TC 020	
OTHERS	<b>EMC IMMUNITY</b>	Compliance to BS EN/EN61000-4-2,3,4,5,6,8,11, BS EN/EN55024,BS EN/EN61547, light industry level, criteria A,EAC TP TC 020	
	<b>MTBF</b>	580.8K hrs min. MIL-HDBK-217F (25°C)	
	<b>DIMENSION</b>	101.6*50.8*26.6mm (L*W*H)	
NOTE	<b>PACKING</b>	0.12Kg; 108pcs/13Kg/0.89CUFT	
	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. Derating may be needed under low input voltage. Please check the static characteristics for more details. 5. Please refer to "DRIVING METHODS OF LED MODULE". 6. The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. 7. Heat Sink HS1,HS2 can not be shorted. 8. Direct connecting to LEDs is suggested, but is not suitable for using additional drivers. 9. To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains. 10. The power supply is considered a component which will be installed into a final equipment. All the EMC tests are been executed by mounting the unit on a 360mm*360mm metal plate with 1mm of thickness. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on <a href="http://www.meanwell.com">http://www.meanwell.com</a> ) ※ Product Liability Disclaimer : For detailed information, please refer to <a href="https://www.meanwell.com/serviceDisclaimer.aspx">https://www.meanwell.com/serviceDisclaimer.aspx</a>		

## ■ Mechanical Specification

Unit:mm



! 1.HS1,HS2 cannot be shorted.  
 2.HS1 must have safety isolation distance with system case.  
 3.M1 is safety ground. For better EMC performance,Please secure an electrical connection between M1,M2,M3, and chassis grounding.

AC Input Connector (CN1) : JST B3P-VH or equivalent


Pin No.	Assignment	Mating Housing	Terminal
1	AC/L	JST VHR or equivalent	JST SVH-21T-P1.1 or equivalent
2	No Pin		
3	AC/N		

DC Output Connector (CN2) : JST B2P-VH or equivalent


Pin No.	Assignment	Mating Housing	Terminal
1	+V	JST VHR or equivalent	JST SVH-21T-P1.1 or equivalent
2	-V		

≡ : Grounding Required


## ■ Block Diagram



## ■ Derating Curve



## ■ Static Characteristics






30W Single Output LED Power Supply

PLP-30 series


### ■ Power Factor Characteristic

#### Constant Current Mode




### ■ EFFICIENCY vs LOAD (48V Model)

PLP-30 series possess superior working efficiency that up to 86.5% can be reached in field applications.



### ■ DRIVING METHODS OF LED MODULE

This LED power supply is suggested to work in constant current mode area (CC) to drive the LEDs.



Typical LED power supply I-V curve

In the constant current region, the highest voltage at the output of the driver depends on the configuration of the end systems.  
Should there be any compatibility issues, please contact MEAN WELL.