



45W Triple Output Switching Power Supply

PT-45 series



■ Features :

- Universal AC input/Full range
- Low leakage current<0.5mA
- Protections: Short circuit / Overload / Over voltage
- Cooling by free air convection
- 100% full load burn-in test
- Fixed switching frequency at 65KHz
- 2 years warranty

User's Manual



UL62368-1

BS EN/EN62368-1



TPTC004


IEC62368-1

CB CE UK

SPECIFICATION

MODEL	PT-45A			PT-45B			PT-45C									
OUTPUT	OUTPUT NUMBER	CH1	CH2	CH3	CH1	CH2	CH3	CH1	CH2	CH3						
	DC VOLTAGE	5V	12V	-5V	5V	12V	-12V	5V	15V	-15V						
	RATED CURRENT	3A	2A	0.3A	3A	2A	0.3A	3A	1.6A	0.3A						
	CURRENT RANGE	0.4 ~ 5A	0.2 ~ 2.5A	0 ~ 0.5A	0.4 ~ 5A	0.2 ~ 2.5A	0 ~ 0.5A	0.4 ~ 5A	0.2 ~ 2.3A	0 ~ 0.5A						
	RATED POWER	40.5W			42.6W			43.5W								
	OUTPUT POWER (max.)	Rated output power for convection; 52W with 18CFM min. Forced air														
	ripple & noise (max.) Note.2	50mVp-p	120mVp-p	50mVp-p	50mVp-p	120mVp-p	100mVp-p	50mVp-p	120mVp-p	100mVp-p						
	VOLTAGE ADJ. RANGE	CH1:4.75 ~ 5.5V														
	VOLTAGE TOLERANCE Note.3	±4.0%	±7.0%	±5.0%	±4.0%	±7.0%	±5.0%	±4.0%	±7.0%	±5.0%						
	LINE REGULATION	±1.0%	±2.0%	±1.0%	±1.0%	±2.0%	±1.0%	±1.0%	±2.0%	±1.0%						
	LOAD REGULATION	±3.0%	±4.0%	±1.0%	±3.0%	±4.0%	±1.0%	±3.0%	±4.0%	±1.0%						
	SETUP, RISE TIME	800ms, 20ms at full load														
	HOLD UP TIME (Typ.)	60ms at full load														
INPUT	VOLTAGE RANGE	90 ~ 264VAC 127 ~ 370VDC														
	FREQUENCY RANGE	47 ~ 440Hz														
	EFFICIENCY (Typ.)	75%			75%			75%								
	AC CURRENT (Typ.)	1A/115VAC 0.7A/230VAC														
	INRUSH CURRENT (Typ.)	COLD START 15A/115VAC 30A/230VAC														
	LEAKAGE CURRENT	<0.75mA														
PROTECTION	OVERLOAD	53 ~ 75W rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed.														
	OVER VOLTAGE	CH1: 5.75 ~ 6.75VDC Protection type : Hiccup mode, recovers automatically after fault condition is removed.														
ENVIRONMENT	WORKING TEMP.	-10 ~ +60°C (Refer to "Derating Curve")														
	WORKING HUMIDITY	20 ~ 90% RH non-condensing														
	STORAGE TEMP., HUMIDITY	-20 ~ +85°C, 10 ~ 95% RH														
	TEMP. COEFFICIENT	±0.04%/°C (0 ~ 50°C) on +5V output														
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes														
SAFETY & EMC (Note 4)	SAFETY STANDARDS	UL62368-1, TUV BS EN/EN62368-1, EAC TP TC 004 approved														
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC 1min.														
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70% RH														
	EMC EMISSION	Compliance to BS EN/EN55032 (CISPR32) Class B, BS EN/EN61000-3-2,-3, EAC TP TC 020														
	EMC IMMUNITY	Compliance to BS EN/EN61000-4-2,3,4,5,6,8,11, BS EN/EN55024, light industry level, criteria A, EAC TP TC 020														
OTHERS	MTBF	288.1K hrs min. MIL-HDBK-217F (25°C)														
	DIMENSION	127*76*28mm (L*W*H)														
	PACKING	0.21Kg; 72pcs/17Kg/1.28CUFT														
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into a final equipment. All the EMC tests are been executed by mounting the unit on a 360mm*360mm metal plate with 1mm of thickness. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on http://www.meanwell.com) 5. Mounting holes M1 and M2 should be grounded for EMI purposes. 6. Heat Sink HS1,HS2 can not be shorted. 7. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft). ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx															

■ Mechanical Specification



AC Input Connector (CN1) : Molex 5277-02 or equivalent

Pin No.	Assignment	Mating Housing	Terminal
1	AC/N	Molex 5195 or equivalent	Molex 5194 or equivalent
2	AC/L		


┌─: Grounding Required

⚠ 1.HS1,HS2 cannot be shorted
2.M1 is safety ground


DC Output Connector (CN2) : Molex 5273-06 or equivalent

Pin No.	Assignment	Mating Housing	Terminal
1	+V		
2,3	+5V	Molex 5195 or equivalent	Molex 5194 or equivalent
4,5	COM		
6	-V		

■ Block Diagram



■ Derating Curve



■ Static Characteristics (B)

